(12)

## **EUROPEAN PATENT APPLICATION**

(43) Date of publication: 27.07.2005 Bulletin 2005/30

(51) Int Cl.7: H04N 5/445

(21) Application number: 05075996.8

(22) Date of filing: 20.05.1994

(84) Designated Contracting States: AT BE CH DE DK ES FR GB GR IE IT LI LU MC NL PT SE

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC: 04075599.3 / 1 443 756 00200915.7 / 1 028 550

(71) Applicant: United Video Properties Inc. Tulsa, Oklahoma 74136-5422 (US) (72) Inventor: The designation of the inventor has not yet been filed

(74) Representative: Neobard, William John Kilburn & Strode 20 Red Lion Street London WC1R 4JP (GB)


Remarks:

This application was filed on 27 - 04 - 2005 as a divisional application to the application mentioned under INID code 62.

# (54) Improved electronic television program schedule guide system and method

(57) An electronic program schadule system which includes a receiver for receiving broadcast, satellite or cablecast television programs for a plurality of television channels and a tuner for tuning a television receiver to a sectled one of the plurality of channels. A data processor receives and stores in a memory television program schedule inforamtion for a plurity of television channels. A user control appartus, such as a remote controller, is utilised by a viewer to choose user control commands and transmit signals in response to the data processor which receives the signals in response to the control commands. A television programs and television.

inforamtion. A video display generator receives video control commands from the data processor and program schedule inforamtion from the memory and displays a portion of the program schedule inforamtion in overlaying relationship with a television program appearing on a television channel in at least one mode of operation of the television programming guide. The operation of the television programming guide. The operation with video display generator with video control commands, issued in response to the user control commands, issued in response to the user control commands, is of display program schedule information for any chosen one of the plurality of television program in overtaying relationship with at least one television program then appearing on any other chosen or of the plurality of channels on the television receiver.



#### Description

Background of the Invention

[0001] This invention relates to an electronic program 5 schedule system, which provides a user with schedule information for broadcast or cablecast programs viewed by the user on a television receiver. More particularly, it relates to an improved electronic program guide that provides the user with a more powerful and convenient operating environment, while, at the same time, increasing the efficiency of navigation by the user through the quide.

[0002] Electronic program guides for television systems are known in the art. For example, one prior system used an electronic character generator to display textual schedule information on the full screen of a television receiver. Other prior systems presented electronically stored program schedule information to a user for viewing while allowing the user to select display formats. Still other systems employed a data processor to input user-selection criteria, then stored only the program schedule information meeting these criteria, and subsequently used the stored information to automatically tune a programmable tuner or activate a recording 25 device at the time of broadcast of the selected television programs. Such prior systems are generally discussed in "Stay Tuned for Smart TV," published in the November 1990 issue of Popular Science.

100031 Collectively, the prior electronic program sysso terms may be difficult to implement and cumbersome to
use. They also fail to provide viewing capabilities that
address in a more realistic manner the viewing habits of
the users of these electronic program systems. Moreover, many of these systems are complex in their design
and are expensive to implement. Ease of use and economy are primary concerns of television program distributors and viewers as they contemplate dramatic increases in the number and nature of program networks
and other television-based services. And, as the
number of television channels available to a user increases dramatically with the advent of new satellite and
cable-based technologies, the utility of these prior systems substantially diminishes.

10004] These prior-art systems also fall to provide the user with sufficient information, for example pricing and the like, about pay-per-view events, premium services or other packaged programming to which the user does not subscribe, nor do they provide the user with the capability to automatically purchase such programming on demand or impulse. Moreover, these prior-art systems are deficient in that they fall to provide an efficient and automatic method of updating or replacing the application software programs that implement the electronic guide at the user sites, relying instead on manual or other or cumbersome forms of revision or replacement or hardware-based systems that can not be updated without physical replacement of inforgrated pricing and/or

other parts.

[0005] Nor do these prior electronic guide systems have the capability of linking the user to other applications or information systems which are not part of the electronic program guide application or data.

[0006] Nor do these prior electronic guide systems provide video promotion of television programs and services that are functionally linked and visually displayed in an integrated fashion. Program promotion is an important element of the effective marketing of television programming. The promotion of pay-per-view pay (i.e., "a la carte") programs and other unregulated program services is particularly important to cable television operators in the wake of re-regulation by the federal government. The current method of promoting such programming using video is through dedicated "barker" channels that use full screen continuous trailers (i.e., previews) which may or may not be accompanied by prices and ordering information. Recently, such promotional videos have been shown in split screens where part of the screen shows general schedule information for a time period roughly corresponding to the time period during which the general program being promoted is shown. Accordingly, there exists a need for an electronic program guide which can provide improved display and linking of video promotions with program schedule information and order processing functions. [0007] The prior electronic program guides also fall to provide the user with a simple and efficient method of controlling access to individual channels and individual programs. The amount of adult situations involving sex and violence has steadily increased during the last 40 years. The issue of how this affects children or other viewers has gained national attention. Providing a parent with the ability to lock-out a channel is a well known and widespread feature of certain television receivers and cable converter boxes. Despite this availability, the feature is seldom used by parents. The main impediments to its effective use are the cumbersome ways in which it is generally implemented, as well as the requirement that entire channels be blocked in order to block access to any objectional programming. A channel-oriented parental lock is unfair to other programmers on the blocked channel -- who, for example, offer adult-oriented programming in the evening and youth-oriented programming the following morning--and inconvenient for viewers who want access to such programs. Thus, there is a particular need for a system which provides password control to individual programs and channels using a flexible and uncomplicated on-screen user interface

[0008] The prior electronic program guides are also deficient in that they do not provide the user with the ability to view on demand current billing status and, thus, a need exists for a system which can provide the user with current billing information on the user's demand. [0009] An additional problem with prior program guides is that when displaying schedule information in

grid format, i.e., columns representing time slots and rows representing channels, program titles generally are width-wise truncated to fit into the cells of the grid. The width of a grid cell varies with the duration of the program. Since a 30 minute program is allotted only a small amount of space for the program title and description, titles and/or descriptions for half and even full hour programs often must be truncated in order to fit into the allotted space. Some systems simply cut off the description of a program without abbreviating it in any way, such that the user is unable to determine the subject matter of the program. For example, a recent television program display included the following text in a grid cell: "Baseball: Yankees v." Although some systems partially alleviate this problem by providing two lines of text in each grid cell, this solution is not ideal because program

descriptions may still be truncated.

[0010] A similar problem arises as the time stots change, either automatically or in response to a user control command. Typically, 90 minutes of schedule information is displayed at one time and the 90 minute window is shiftable in 30-minute increments. In the case where a 30 minute shift causes a 30 minute size grid cell to display, e.g., a two-hour movie, it is likely that the full title of the movie will not it into the cell. Truncation 5 of the title is thus required in this situation as well, in this case, while two himse of text may be desirable to fit the title in the 30 minute cell, the 60 and 30 minute cells may require only one line of text to delay the title.

[0011] The prior electronic program guides also lack 30 a method for creating a viewing itinerary electronically while still viewing a program currently appearing on the television receiver. Moreover, these prior program guides leave much guess work for the user as he navigates through a sequence of channels. When skimming 35 through channels to ascertain the program then being displayed on any channel, commonly known as "channel surfing," the user needs to guess which program is currently being aired from the video encountered as the user surfs through the channels. Since much -- in some cases, up to 30% - of the programming appearing on any given channel at any given time is advertising or other commercial programming, the user is not provided with any clues as to what program is appearing on a selected channel at a given time and must therefore wait until the advertisement or commercial is over before ascertaining the program then appearing on the selected channel. Thus a need exists for a program guide which displays current program schedule information for each channel as the user surfs through the available channels.

[0012] Accordingly, there is a need in the art or a simplified electroin program schedule system that may be more easily implemented, and which is appealing and efficient in operation. There is also a need to provide the user with an electronic program schedule system that displays both broadcast programs and electronic schedule information in amaner not proviously available with other electronic program schedule systems, particularly those using a remote controller.

[0013] For example, there is a particular need for a liaxible program schedule system that allows a user to view selected broadcast programs on a portion of the screen of the television receiver while simultaneously viewing program schedule information for other channels and/or services on another portion of the screen. There is also a need for such a program schedule sys-

There is also a freetu for such a program schedule system that permits the user to select from a plurality of selectable display formats for viewing the program schedule information. It is also preterred to have a system that indicates to the user those keys on the remote controller that are active in any particular mode of operation. There also exists a need for such a system that will give a user the capability to set a programmable reminder for viewing a program scheduled to air at a future time.

[0014] There is also a need for an electronic guide system providing the user with comprehensive information about pay-per-view events, premium services or other packaged programming to which the user does not ordinarily subscribe, and which provides the user with the capability to automatically purchase such programming on demand or impulse. There is also a need for an electronic guide system providing a reliable and efficient method of updating or replacing the application software that implements the electronic guide at the user sites. [0015] There also exists a need for an electronic or such as the provided of the provided of

[0015] There also exists a need for an electronic program guide that operates as a shell or window to provide the user with the capability to access other applications or information systems that are not part of the electronic program guide application or data.

[0016] It is accordingly an object of the present invension to prowde a system that will allow the user to view a broadcast program while, at the same time, interactively viewing program schedule information for other programs.

[0017] It is another object of the present invention to provide the user with the ability to select from among a plurality of display formats for the program schedule information.

[0018] It is yet another object of the present invention to indicate to the user of the program schedule system those keys on the remote controller active in the particular mode of operation of the system at the time of use. [0019] It is a still further object of the present invention to provide the user of the electronic program schedule system with the capability of setting programmable reminder messages for any future program.

[0020] It is yet a further object of this invention to provide the system user with comprehensive information about pay-per-view events, premium services or other packaged programming to which the user does not subscribe and the capability to automatically purchase such programming on demand or impulse.

[0021] It is another object of the present invention to provide an electronic guide system that provides a reli-

able and efficient method of updating or replacing the application software programs that implement the electronic guide at the user sites.

[0022] It is still another object of the electronic program guide to operate as a shell or window to provide the user with the capability to access other applications or information systems which are not part of the electronic program guide application or data.

[0023] It is yet another object of the electronic program guide to provide a system whereby video promotion of television programs and services are functionally linked and visually displayed in an integrated fashion to facilitate the marketing and sale of such programs and services.

[0024] It is still a further object of the present invention 15 to provide password control for access to individual programs, as well as channels, using a protected interactive flexible and uncomplicated on-screen interface.

[0025] Another object of the present invention is to provide the user with current programming information 20 for all programs as the user surfs through the available channels.

[0026] It is yet a further object of the present invention to provide a system in which the user can access his current billing information on demand.

[0027] It is another object of the present invention to provide a system which overlays television program listings against varying background views.

[0028] It is yet another object of the present invention to provide an improved display of text in the grid cells 30 comprising a page of television program listings.

[0029] These and other objects of the invention are achieved by an electronic program schedule system which includes a receiver for receiving broadcast, satellite or cablecast television programs for a plurality of 35 television channels and a tuner for tuning a television receiver to a selected one of the plurality of channels. A data processor receives and stores in a memory television program schedule information for a plurality of television programs to appear on the plurality of television channels. A user control apparatus, such as a remote controller, is utilized by a viewer to choose user control commands and transmit signals in response to the data processor which receives the signals in response to user control commands. A television receiver is used to display the television programs and television program schedule and other information. A video display generator receives video control commands from the data processor and program schedule information from the memory and displays a portion of the program schedule information in overlaying relationship with a television program appearing on a television channel in at least one mode of operation of the television programming guide. The data processor controls the video display generator with video control commands, issued in response to the user control commands, to display program schedule information for any chosen one of the plurality of television programs in overlaying relationship

with at least one television program then appearing on any chosen one of the plurality of channels on the television receiver.

- [0030] According to a further aspect of the invention there is provided a method of operating an electronic television program guide, which method includes providing a user with input means by which a request for help information can be entered, and responding to said request by providing said information.
- [0031] Said guide may have a plurality of operating modes between which it can be switched.

[0032] Said guide may have a mode (FLIP) in which whenever the user changes the program channel a graphic overlay containing schedule information for the currently tuned channel is superimposed on the received program signal.

[0033] While said guide is in said mode (FLIP) the graphic overlay may be removed if the user does not issue a change-channel instruction or other command within a predetermined time interval.

[0034] Said mode (FLIP) may be the default mode. [0035] Said guide may have a mode (BROWSE) in which the user can select a channel without changing the currently tuned-channel and whenever the user selects a program channel a graphic overlay containing schedule information for the selected channel is super-imposed on the received program signal for the currently tuned channel.

[0036] The user may select the channel using directional arrow keys.

[0037] The user may select between schedule information for the current time and for a future time using directional arrow keys.

[0038] The user may select a reminder concerning transmission of a program at a future time to be displayed on an overlay.

[0039] The user may tune to the selected channel using an ENTER key.

[0040] The graphic overlay may include a small video window for showing a video signal corresponding to the schedule information in the overlay.

[0041] While said guide is in said mode (BROWSE) the graphic overlay may be removed if the user does not issue a select-channel instruction or other command within the predetermined time interval.

[0042] Said guide may have a mode in which the program schedule information is displayed in a grid listing or as a single-column grid-like display.

[0043] Said guide may have a mode in which the user can select pay-per-view events or services, specialized programming or premium service programs.

[0044] Said guide may have a mode (MENU) in which the user can select program schedule information display format and other on-line information services.

55 [0045] Upon an entry of a request for help information a user may be asked to identify a portion of the program guide about which he or she would like to receive the help information. [0046] A sub-menu may be displayed that enables the user to identify the particular portion of the program guide about which he would like to receive the help information.

[0047] Upon entry of a request for help, information may be displayed that depends on the state of said guide at which the user has entered said request.

[0048] The guide may have a plurality of operating points, and the method further comprise tracking a current operating point in the plurality of operating points, and providing context-sensitive help based on the current operating point.

[0049] The input means may comprise a user-selectable icon or a help key.

[0050] The help information may be a text message, 15 an instructional audio program, or an instructional video program.

[0051] The help information may be stored in memory.
[0052] The method may be carried out with one or
more of a broadcast television transmission, a cable television transmission and a satellite transmission.

[0053] In another aspect of the invention, there is provided electronic television program guide apparatus containing a program for implementing the method of the further aspect.

[0054] In a still further aspect the invention provides an electronic television program guide system for providing help information for explaining to a user of an electronic television program guide how said guide operates, said system comprising:

means for providing a user with an opportunity to access help information for a portion of an electronic television program guide, and means for providing help information that explains to the user how a sportion of the electronic television program guide operates.

[0055] In yet a further aspect the invention provides an electronic television program guide system for providing their information for explaining to a user how said guide operates, said system comprising a video generator, a remote controller, a microcontroller, and an electronic television program guide for execution by the microcontroller and programmed to (1) provide the user with an opportunity to access help information for a portion of the electronic program guide using a remote controller, and (2) provide to the video display generator for display their information for explaining to the user how the portion of said guide operates.

[0056] The system may further comprise a television.

[0057] In yet another aspect the invention relates to
an electronic television program guide for use in connection with a television receiver for displaying a plurality of television programs from a plurality of program 55
sources on a plurality of user-selectable television channels, comprising: user control means for issuing control
commands including channel-control commands; data

processing means for receiving said control commands and for generating video control commands; a video display generator adapted to receive video control commands from said data processing means for generating a location menu on said television receiver, said location menu identifying for a user one of a plurality of program sources associated with each of said plurality of television commands; and selection means for allowing said user to select any one of said plurality of television commands; and selection means is adapted to the said location menu; said data processing means being responsive to said selection means and adapted to tune said television receiver to the television channels elected by the user in said location.

[0058] In another aspect the invention provides an electronic television program guide for use in connection with a television receiver for displaying a plurality of program sources on a plurality of user-selectable television channels, comprising: user control means for issuing control commands including program schedule display control commands; storage means for electronically storing television program schedule information for a plurality of television programs, said program schedule information comprising program title information, said program title information comprising a predetermined abbreviated title for at least one of said plurality of television programs; data processing means for receiving said user commands, retrieving said program schedule information, and generating video display generator control commands, said data processing means being adapted to receive said predetermined abbreviated title in response to said user control commands; a video display generator adapted to receive video control commands from said data processing means for generating a display of television program schedule listings, said display of program listings comprising program schedule information for at least one channel and at least one time period, said display further comprising an

[0059] In yet another aspect the invention provides an electronic television program guide for use in connection with a television receiver for displaying a plurality of program sources on a plurality of user-selectable television channels, comprising: user control means for issuing control commands including program schedule display control commands, said program schedule display control commands including background display control commands; storage means for electronically storing television program schedule information for a plurality of television programs, said storage means being further arranged to store a plurality of user-selectable background views; data processing means for receiving said user control commands, retrieving said program schedule information and said user selectable background view, and generating video display generator control commands; a video display generator adapted to receive video control commands from said data processing means for generating a display of tele-

abbreviated title.

10

vision program schedule listings, said display of program listings comprising program schedule information for at least one channel and at least one time period, said video display generator being further adapted to display said program listings in overlaying relationship with said background view.

### Brief Description of the Drawings

#### [0060]

- Fig. 1 is a block diagram showing various components of the preferred embodiment of the invention herein.
- Fig. 2 is a block diagram showing the combination of program and schedule information by the video overlay device utilized in the preferred embodiment of the invention.
- Fig. 3 depicts a remote controller that can be used in connection with the preferred embodiment of the electronic program guide system of the present application.
- Fig. 4 depicts an alternative embodiment of the remote controller shown in Fig. 3.
- Fig. 5 shows an overlay appearing on a television 25 screen in one mode of operation of the preferred embodiment of the present invention.
- Fig. 6 is a menu that appears on a television screen in a MENU mode of operation of the preferred embodiment of the present invention.
- Fig. 6A is yet another menu that appears on a television screen in a MENU mode of operation of the preferred embodiment of the present invention.

  Fig. 7 depicts a Viewer Preference Menu that appears on a television screen in one aspect of the
- preferred embodiment of the present invention.
  Fig. 8 shows a Preferred Channel selection sub-
- Fig. 9 shows an impulse ordering menu that appears on a television screen in one aspect of the
- preferred embodiment of the present invention.
  Fig. 10 shows a Premium Services submenu that appears in one mode of operation of the preferred embodiment of the present invention.
- Fig. 11 shows a graphic overlay appearing on a telewision screen in a BROWSE mode of operation of the preferred embodiment of the present invention. Fig. 12 shows a graphic overlay appearing on a television screen in a BROWSE mode of operation of the preferred embodiment of the present invention having different information from that shown in Fig.
- Fig. 12A shows a graphic overlay appearing on a television screen in a BROWSE mode of operation in the present invention displaying schedule information for a time and channel other than that shown in Fig. 11.
- Fig. 13 shows a graphic overlay appearing in a RE-

- MINDER mode of operation of the preferred embodiment of the present invention.
- Fig. 14 shows yet another graphic overlay appearing in a REMINDER mode of operation of the preferred embodiment of the present invention.
  - Fig. 15 is yet another menu that appears on a television screen in a MENU mode of operation of the preferred embodiment of the present invention.
  - Fig. 16 is yet another menu that appears on a television screen in a MENU mode of operation of the preferred embodiment of the present invention.
  - Fig. 17 is yet another menu that appears on a television screen in a MENU mode of operation of the preferred embodiment of the present invention.
- preferred embodiment of the present invention. Fig. 18 shows a grid listing of schedule information displayed in an All Listings mode of operation of the preferred embodiment of the present invention.
- Fig. 19 shows schedule information displayed in a Listings By Category mode of operation of the preferred embodiment of the present invention.
  - Fig. 20 shows schedule information displayed in a Listings By Channel mode of operation of the preferred embodiment of the present invention.
  - Fig. 21 shows information displayed in response to a user's request for supplemental programming information.
  - Fig. 22 shows programming, ordering and video promotional information displayed in a Pay-Per-View mode of operation of the preferred embodiment of the present invention.
  - Fig. 23 shows an ordering submenu used in conjunction with the mode of operation shown in Fig. 22.
  - Fig. 24 shows yet another ordering submenu used in conjunction with the mode of operation shown in Fig. 22.
  - Fig. 24A shows yet another ordering submenu used in conjunction with the mode of operation shown in Fig. 22.
  - Fig. 25 shows another grid listing of schedule information displayed in an All Listings mode of operation of the present invention.
- Fig. 26 shows a Premium Services submenu that appears in one mode of operation of the preferred embodiment of the present invention.
  - Fig. 27 shows a messages menu that appears in one mode of operation of the preferred embodiment of the present invention.
  - Fig. 28 shows exemplary messages used in connection with the menu of Fig. 27. Fig. 28A is an alternative message menu.
  - Fig. 29 shows billing information used in connection with the menu of Fig. 27.
- Fig. 30 shows a Key Lock Access menu that appears during one mode of operation of the preferred embodiment of the present invention.
  - Fig. 31 shows a menu appearing in connection with an Interactive Television mode of operation of the

preferred embodiment of the present invention.

Fig. 32 shows information that appears in a Quote Watch menu in connection with the Interactive Tel-

Watch menu in connection with the Interactive Television mode of operation shown in Fig. 31.

Fig. 33 shows other information that appears in connection with the Interactive Television mode of operation shown in Fig. 31.

Fig. 34 is a menu showing information that appears in a news display in the Interactive Television mode of operation of the preferred embodiment of the present invention.

Fig. 35 is a menu showing information that appears in a sports display in the Interactive Television mode of operation of the preferred embodiment of the present invention.

Fig. 36 is a flow chart showing the operation logic required for implementation of a computer program for the electronic program guide.

Fig. 37 is a menu showing a Locator screen for locating channel numbers and defining favorite channel lists.

Fig. 38 is an alternative menu that can be used in a MENU mode of operation of the electronic program guide.

Fig. 38A and 38B show, respectively, an alternative 2s main menu screen and a listing-by-time screen accessible from the alternative main menu.

Fig. 39 is a Lockout menu that alternatively can be used for permitting or prohibiting access to certain programs.

Fig. 40 is a Setup menu that can be used to set text location and a purchase code for premium and payper-view programming.

Fig. 40A shows an exemplary menu for inputting a lockout code.

Figs. 40B through 40E show, respectively, exemplary menus for entering, confirming, clearing or changing a purchase code.

Fig. 41 is a Lockout Verify menu that is used in connection with the Lockout menu of Fig. 39. Fig. 42 is a flow chart showing the operation of the

Fig. 42 is a flow chart showing the operation of the preferred embodiment of the text fit system of the invention herein.

# DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

#### System configuration

[0051] Fig. 1 is a block diagram showing various components of the electronic program schedule system generally designated as 10. Physically, these system components can be located in a user's set-top cable components can be located in a user's set-top cable components can be mounted in a separate housing, or included as part of a television receiver. Notice, personal computer, or multimedia player, or reside as a distribution computer, or multimedia player, or reside as a distribution of the program of the pro

ed application in a broadband network architecture.

[0062] An input signal 11 is connected to a receiver

12, which receives a transmitted data stream from a data provider. The data stream may contain, for example, 5 information about programs or services a variable in a particular market, geographical or otherwise. The input signal 11 can originate, for example, as part of a standard broadcast, cablecast or satellite transmission, or other form of data transmission. The data provider is a 10 program information provider, the satellite uplink manager, a local cable operator, or a combination of these sources, and the data stream contains program schedule information for all television programs and other less increases and the cable programs of the control of these sources, and the data stream contains program schedule information for all television programs and other services available in the operator's geographical mar-

[0063] The data stream may be modulated and then transmitted on the cable line in any number of ways, including as part of a dedicated channel transmission operating at a frequency of, for example, 75 MHz. Those of skill in the art will understand that numerous other transmission schemes can be used to transmit the data stream, such as embedding it in the vertical blanking interval of a program broadcast signal. As will be discussed in greater detail below, according to the present invention, the transmitted data stream may additionally contain application software for implementing or updating the electronic program guide at the user site.

[0064] The transmitted program schedule data or application software is received by the receiver 12 on sigplication software is received signal is passed from the receiver to a data demodulator 13, such as a QPSK demodulator or a GI Info-Cipher 1000R, which demodulates the transmission and passes it to a buffer 15. [0065] Amicrocontroller 16, such as a M66000EC, re-

35 ceives data passed to the buffer I 5 Bootstrap operating software, which may be used for capturing electronic program guide application software updates, is stored in a read only memory (ROM) 17. The microcontroller 16 uses the received program schedule information to 40 build a database by storing the data in appropriately organized records in dynamic random access memory (DRAM) 18. The stored schedule information can be updated on a periodic basis, such as hourly, daily or week, by, or at any time when changes in scheduling or other 45 factors warrant an update. The system also includes a system clock 19.

[0066] Alternatively, the program schedule information could be supplied in a ROM, disk or other non-voiatile memory, or it could be downloaded to a storage disk or other data storage device. The invention herein is not directed to the particular method of transmission or reception of the schedule information.

[0067] If the microcontroller 16 recognizes the received data as application software which controls the program schedule system, as opposed to program schedule information, it stores it in non-volatile memory, such as an electricality erasable programmable ROM (EEPROM) 20 or battery-backed static RAM (SRAM). This configuration allows revised or replacement versions of the application software to be downloaded directly from the software developer to the user site through the cable or other transmission system.

[0068] In the case where an EEPROM is utilized, revised or replacement versions of the application software downloaded from the developer are first stored in DRAM 18 by the microcontroller 16, under direction of the downloading operating software stored in the ROM 17. The stored application software can then be checked for accuracy by, for example, a checksum analysis or other verification routine.

[0069] After the accuracy of the application software has been verified, the microcontoller 16 initiates a routine to re-program the EEPROM 20, where the application software is permanently stored. The microcontroller 18 will issue proper control commands to a reprogram circuit 21, which is adapted to supply the proper program oricuit 21, which is adapted to supply the proper program ovitage and logic control signates 22 required to erase and write to the EEPROM. It supplies this program voltage, vprog, as well as any other required control signals, such as read or write enable, to the EEPROM 20 upon command from the microcontroller 16. After the EEPROM 20 has been electrically erased, the microcontroller 16 influitates transfer of the new application 25 software from the DRAM 18 to the EEPROM 20 for storing.

[0070] When a battery-backed SRAM is utilized as non-volatile memory, the microcontroller stores the revised or replacement version of the application software downloaded from the developer directly in the SRAM, again under direction of the downloading operating software stored in the ROM. The stored application software can then be checked for accuracy by, for example, a checksum analysis or other verification routine.

[0071] When power is first applied to the system 10, the bootstrap operating software verifies that the program guide application software is resident in memory. If it is not resident, the bootstrap operating software waits for a download of the software. Once the applica- 40 tion software is resident, the microcontroller 16 executes the application program software from a dedicated portion of the DRAM 18. Alternatively, the application software can be executed directly from the non-volatile memory 20. Under control of the program guide application software, the microcontroller 16 first verifies that the program schedule information is resident in DRAM 18. If it is not resident, the microcontroller waits for a download of the program schedule information, as discussed above. Alternatively, if the application program is resident in memory, but the database records containing the program schedule information data are not yet available, the application software can be configured to carry out other tasks, such as allowing the user to carry out functions not requiring the program schedule information data, as well as displaying an appropriate message indicating the database data is not yet available. [0072] When the schedule system is operating, as

discussed in greater detail hereinbelow, the microcontroller 16 takes the program schedule information stored in the DRAM 18 and, in conjunction with other downloaded data types such as stored bit maps for the screen configuration and the graphic symbol or logo displays stored in non-volatile memory 20 or, alternatively, in DRAM 18, supplies it to a video display generator (VDG) 23, which in the present embodiment may be a commercially available VGA-type graphics card, such as a Rocgen card manufactured by Roctec. The VDG includes a standard RGB video generator 24, which takes the digital program schedule information sent by the microcontroller 16 and converts it to an RGB format in accordance with the bit map for the particular screen display then being presented to the user on the television receiver 27. The configuration of each screen is shown and discussed in greater detail in the System Operation section below.

[0073] The VDG also includes a Video Overlay Device 25, which accepts the RGB video input, as well as an input from conventional television tuner 28, such as a conventional tuner manufactured by General Instrument or a Jerrold DPBB tuner, which supplies a program signal in standard NTSC video format. The overlay device 25 converts and combines the RGB signal with the signal from the tuner 28, and produces a composite NT-SC output signal containing both the program signal and the program schedule information, as shown in Fig. 2. This composite video signal is supplied to a modulator 26, shown in Fig. 1, which can be a modulator such as available from Radio Shack, and then to the television receiver 27, which the user keeps tuned to the modulated channel, for example, channel 3 or 4. The composite video signal can also be supplied directly to the television receiver 27 or other receiving device from the VDG through a video port 25A on the VDG.

[0074] The system components identified in connection with Fig. 1 can all be implemented in a preferred platform by, for example, an IBM personal computer equipped with a transmission link and a video graphics card, such as those manufactured by Roctec. Other platforms, such as a cable converter box equipped with a microprocessor and memory, or a broadband network also could be used. Examples of the particular components are as follows: Microcontroller -- Motorola part no. MC68331-16; ROM -- Texas Instruments part no. TMS27PC512; DRAM -- Texas Instruments part no. TM4256; EEPROM -- Intel part no. 28F001BX-T. in any event, those of skill in the art will appreciate that the particular details of the hardware components and data storage are a function of the particular implementation of the system, and are not the subject of the present invention.

[0075] As discussed in detail below, the user may navigate through the program schedule system with a remote controller, such as that shown in Fig. 3, which operates on conventional principles of remote control transmitter-receiver logic, such as by infrared or other.

signalling, or other suitable user interface. The remote controller 31 communicates with the microcontroller 16 through the remote controller receiver 29, shown in Fig. 1, which can be a Silent Partner IR receiver and which receives signals transmitted by the remote controller 31 and supplies the microcontroller 16 with a corresponding digital signal indicating the key depressed by the user.

[0076] A remote controller suitable for the present invention, such as shown in Fig. 3, which can be a remote controller manufactured by Universal Electronics or Presentation Electronics Silent Partner, may include a power swich 32, volume 33 and mute 34 controlls, an ENTER key 35, 0-9 digit keys 36, four direction arrow keys 37A and 37B, a MODE key 38 and an information 15 key 39 that is designated with a lower case 1.1 The power 22, volume 33 and mute 34 keys operate in the same manner as conventional remote controllers bytically used with present-day television receivers. The numeric digit keys 36 also function in much the same manner as conventional remote controllers. A brief description of the remaining keys follows.

[0077] The MODE key 38 takes the user through various layers of the electronic program schedule system 10 and generally allows the user to return to a previous 25 screen when he is in a submenu. The up/down direction arrow keys 37A allow a user to navigate through the different TV program channels when the program schedule system is in a FLIP or BROWSE mode, as will be fully described below, and also allow the user to navigate through highlighted bars displayed on the TV screen when in a MENU mode. The left/right direction arrow keys 37B allow the user to navigate through selected time periods when the program schedule system is in the BROWSE mode, as will also be described below. They further allow the user to navigate across subject-matter categories while in the "Categories" submenu of the MENU mode, as well as to navigate across time periods when the program schedule system is in a pay-per-view ordering mode and, in general, navigate in left or right directions to select various icons and other objects. The information, or "i," key 3 9 allows the user to view supplemental program and other information during the various modes of the program schedule system. The ENTER 35 key fulfills and inputs a command once the user has made a selection from the remote controller keys. The function and operation of these keys will be made more apparent in the detailed discus-

sion of the FLIP, BROWSE and MENU modes below. [0078] A second embodiment of the remote controller 40 is shown in Fig. 4. This embodiment of the remote controller also includes a power key 41, numeric digit keys 42, direction arrow keys 43 and 43B, information keys 48, ENTER or SELECT or "OK" key 44, volume control 45, lockout key 45A, mute keys 46 and-hejk key 48A, it also includes pound sign and star keys.

[0079] This embodiment of the remote controller further includes a number of icon keys 47A and 47B, which correspond to different submenus or modes of the program schedule system. The icons 47A and 47B may also be displayed on the TV screen when the program schedule system is operating. The icon keys essentially replace the MODE key 38 used in the embodiment of the remote controller shown in Fig. 3. Using these keys, he user can move from one mode to another simply by depressing the icon key corresponding to the desired mode of operation of the program schedule system. In the embodiment of Fig. 4, the icons 47A and 47B are shown as graphic symbols situated directly above a corresponding color-coded key. Alternatively, the colorcoded keys could be eliminated and keys could be formed in the image of the icon itself.

5 [0080] The embodiment of the remote controller shown in Fig. 4 also includes three color-coded viewer preference or favorite channel keys, 48A, 48B and 48C that are situated directly above the icon keys. Each of these keys indicates to the program schedule system a distinct user-created 'Channel Preference' or 'Favorite Channel' Isis, which is a listing of a specific subset of channels for a particular user, arranged in the sequential order that the user wishes to view during operation of the program schedule system. The creation of the Channel is the sequential order that the user wishes to view during operation of the program schedule system. The creation of the Channel is the sequential order that the user whose view during operation are neither than the sequential order that the user whose view during operation are neither than the sequential order. The creation of the Channel is the sequential order than the sequential order than the sequential order.

[0081] The remote controller of Fig. 4 also may be equipped with a "HELP" key 48A, which, when depressed, causes the microcontroller 16 to retrieve previously stored instruction messages from memory and cause them to be displayed on the television receiver These messages offer help to the user in the form of instructions that guide the user through the operation of the various operating modes of the electronic television program guide. They may be text messages, or instructional video images, or audio programs, depending on the storage capacity of the system, or any combination of these. Moreover, these help messages may be created so that they are context-sensitive, i.e., the messages displayed depend entirely upon the precise point in the operation of the electronic program guide that the user depresses the help key 48A. For example, information could be supplied for operation of the remote controller, for operating the FLIP or BROWSE mode (discussed below), or any other mode of operation of the guide, for impulse ordering, for setting a lockout, etc. In order to accomplish this, each point of operation of the guide could be coded so that the microprocessor could track the current operating point, for example, by temporarily storing the code reflecting the present operating point as the user operated the guide. When the user pressed the help key 48A, the microcontroller 16 would retrieve an appropriate set of messages based on the presently stored operating point code. Additionally, the I key 39 could be used to carry cut the function of the help key.

[0082] Additionally, each of the functions of the remote controllers can also be integrated into a keypad on the user's cable box or other hardware.

#### System Operation

[0083] In operation, the electronic program schedule system of the present invention functions as follows.

#### FLIP Mode

[0084] When the user is viewing a particular program channel on the television receiver, the program schedule system defaults to a FLIP mode, shown in Fig. 5. In this mode, a graphic overlay 51 containing programming 15 information for the channel currently tuned on the tuner is superimposed in overlaying relationship with a received program signal 55 on the screen of the television receiver 27 whenever the viewer changes the program channel, for example, by using the up/down direction ar- 20 rows on the remote controller. The video overlay device 25, such as shown in Fig. 1, combines the computergenerated RGB video-graphic overlay information with the NTSC-format program signal from the tuner 28, and supplies an NTSC-format output signal, which includes 25 the program signal from the tuner and the program schedule overlay information for viewing on the television receiver 27.

[0085] The programming information contained in the graphic overlay 51 is supplied to the RGB video gener- 30 ator by the microcontroller. In FLIP mode, the microcontroller first searches the program schedule database in, for example, the DRAM 18 to retrieve the programming information for the currently tuned channel 52 corresponding to the current time; i.e., the time at which the user just turned on the television receiver for viewing. The microcontroller 16 then supplies the current channel and program information to the RGB video generator 24 which converts the digital data information to RGB format and supplies it to the video overlay device 25. [0086] In normal operation, the microcontroller 16 defaults to displaying all channels offered by the cable company prioritized by numeric order, which is determined by the broadcast channel position in the radio spectrum or the marketing judgments of local cable operators. Using a "Channel Preference" submenu, or an alternative "Locator" screen, both of which are discussed below, the user can revise the content and/or sequential order of the channels presented to the television receiver 27.

[0087] In general, if the user does not issue a changechannel instruction, or other command. from the remote controller 40 within a predetermined time interval while in the FLIP mode, the microcontroller is instructs the VDG 23 to remove the graphic overfay 51 from the totewision receiver; thus presenting only a program signal 55 to the television receiver 27 for viewing. The duration of the predetermined time interval is such that it allows

the user sufficient time to read the programming information contained in the overlay. The duration of the predetermined time interval during which the graphic 51 overlay appears is stored in a location in non-volatile memory 20 addressable by the microcontroller 16. The user can change the duration of the time interval, by first entering a Viewer Preference mode, and then selecting an "overlay interval" entry. The microcontroller 16 then causes a user prompt to be displayed on the screen which, for example, asks the user to select an appropriate time period for displaying in the graphic overlay on the screen. Using the numeric keys, the user can input an appropriate response, for example, a period between 5 and 60 seconds, and then depress ENTER. The new interval period is then read and stored by the microcontroller 16 in the overlay time interval location in memory. [0088] If the user issues a change-channel command from the remote controller 40 before or after the predetermined overlay period has elapsed, either by using the up/down direction arrows 43A, or by entering a desired channel number using the numeric keys 42 and then depressing the ENTER key 44, the microcontroller 16 will cause the tuner 28 to tune to the desired channel --either the channel immediately preceding or following the current channel when the up or down arrow 43A is used or the specific channel entered on the numeric key pad by the user -- and will also search for and immediately cause to be displayed the current program information for that channel. Thus, as the user flips through the channels, the program schedule information for any selected channel automatically appears in the graphic overlay 51 while the actual program 55 appearing on the selected channel at the particular time occupies the remainder of the screen.

[0089] The system can also be configured to issue an error message, such as an audible beep or displayed text indicating an invalid key stroke, if the user depresses either the left or right direction arrow keys while in the FLIP mode.

#### BROWSE Mode

[0090] To initiate the BROWSE mode, the user depresses the MODE switch once while in the FLIP mode when using the first embodiment of the remote controller 31 shown in Fig. 3. Utilizing the second embodiment of the remote controller 43 shown in Fig. 4, the user his fig. 4, the user hold depress the button below the BROWSE floor 47A. [0091] in the BROWSE mode, the user is provided

with the ability to scan through program schedule information for any channel, including, but not limited to, the channel being viewed, while at the same time continuing to view the TV program previously selected. As shown in Fig. 11, in this mode the graphic overay information that appears in the FLIP mode is replaced with programing information for the channel being prowsed, which may or may not be the channel currently being viewed by the user. After the user issues the command from the

remote controller 40 to enter the BROWSE mode, a graphic overlay 111 is generated, as in the FLIP mode, with program schedule information for the currently tuned channel 112 and a textual BROWSE indicator 113 to remind the user of the currently active mode, as shown in Fig. 11.

[0092] If the user depresses either the up or down direction arrow on the remote controller 40 while in the BROWSE mode, program schedule information for either the prior or next channel is displayed in the graphic overlay portion 111 of the television receiver screen 27. while the tuner remains tuned to the channel program that appeared on the television receiver at the time the user entered the BROWSE mode, as shown in Fig. 12, and continues to so appear. Each successive depression of the up or down direction arrow key produces corresponding program schedule information for the selected channel. The graphic overlay may also include a small video window for showing the actual video signal of a currently aired program or a clip of a future program 20 corresponding to the schedule information then appearing in the BROWSE overlay. In this way, the user can simultaneously scan program schedule information for all channels while continuously viewing at least one selected program on the television receiver. With the ad- 25 vent of sophisticated television receivers, it may also be possible to simultaneously display multiple broadcast programs on a single screen for viewing, or to split the screen to show, for example, broadcast programs in combination with advertisements. The BROWSE fea- 30 ture could be used in any of these situations.

[0093] If, at any time during scanning of the program schedule information in the BROWSE mode, the user desires to tune the television receiver 27 from the program channel currently being viewed to the program 35 channel indicated in the schedule information in the graphic overlay, he simply depresses the ENTER button. 44 and the tuner 28 will be tuned to that channel. If the user does not want to view another channel and wishes to exit the BROWSE mode, thus removing the graphic overlay 111 with the program schedule information, he must depress the MODE key twice in the first embodiment of the remote controller 31. The first depression of the MODE key takes the user to the MENU mode, discussed below, and the second depression will take the user to the FLIP mode. Once in the FLIP mode, the graphic overlay will be removed after the duration of the time-out interval has passed. In the second embodiment of the remote controller shown in Fig. 4, the user toggles the BROWSE icon key to deactivate the BROWSE mode.

[0094] When the user first enters the BROWSE mode and begins scanning channels, the schedule information appearing in the overlay portion 111 describes the programs currently playing on any particular channel. In order to vew programming information for later or programming information for later or redirections, the user employs the left and right direction arrows 43B. As a consequence, the system will display

future program schedule information for the particular channel previously selected by the up and down direction arrows, whether it is the channel currently being viewed or any other available channel. The schedule information presented includes the name of the program and program start/stop time. The instant embodiment of the system, in order to conserve memory, will not allow the user to view programming information for a time prior to the current time. The system could be easily modified to provide such information if adequate memory is made available. It may be desirable, for example, to allow a user to view schedule information for an earlier time to find a particular show and then allow the user to command the microcontroller to find and display future airing dates of the show, or the microcontroller could simply do this automatically.

0095] When viewing program schedule information for a future time in the BROWSE mode, the displayed time of airing 120 of the particular show 122 is highlight-12 ed, as well as the channel number and service indicator 123, as shown in Fig. 12A. Such highlighted information reminds the user that he is viewing program schedule information for a future time. Also, when viewing program schedule information for a future time on any particular channel in the BROWSE mode, depression of the channel up direction arrow key on the remote controller 40 causes programming schedule information for the next channel to appear, which corresponds in time to the future time that was being viewed before the up key was depressed by the user. The channel down direction arrow key 435 functions identically in this mode.

[0096] If while viewing program schedule information for a future time in BROWSE mode the user depresses the ENTER key on the remote controller, the microcontroller 16 will instruct the VDG 23 to display a REMIND-ER overlay message 130 which, as shown in Fig. 13, is displayed as a second overlay 131 appearing above the BROWSE overlay 132. The REMINDER message 130 queries the user as to whether the system should remind the user, at a predetermined time before the start of the selected program, that he or she would like to view the selected program, as shown in Fig. 13. If the user responds affirmatively, the microcontroller 16 stores reminder data consisting of at least the channel, time and day of the selected program in a reminder buffer, which contains similar schedule information for all programs for which the user has set a reminder. At a pre-determined time before the selected program start time, for example, five minutes, the microcontroller 16 will retrieve schedule information, including title and service. based on the reminder data, and will instruct the VDG 23 to display a REMINDER overlay message 140 on the television receiver 27, as shown in Fig. 14, to remind the user that he or she previously set a reminder to watch the selected program. The REMINDER message 140 contains the channel, service and start time. It also displays the number of minutes before the time of airing of the particular show and updates the display every

minute until the time of airing. The REMINDER message 140 also displays a "TUNE" inquiry, which asks the user if she would like to tune to the selected program. When the user sets multiple reminders, the reminder overlays are stacked, for example, in ascending order according to the time each reminder is scheduled to be displayed, and the next reminder message will appear on the television receiver after the user takes appropriate action to remove the reminder message then being displayed. The REMINDER message (140 could also be adapted to allow the user to display or modify a list of all reminders previously set by the user. As with the overlay display time period in the FLIP mode, the user can modify the time period before a selected program that the RE-MINDER message appears by entering the Viewer Preference mode and revising the time entry.

#### MENU Mode

[0097] Using the remote controller 31 shown in Fig. 3, the user can enter the MENU mode from the BROWSE mode or from the FLIP mode by toggling the MODE button 38 once or twice, respectively. Using the remote controller 40 of Fig. 4, the user would simply depress the key 478 corresponding to the MENU icon.

[0098] Referring to Fig. 6, in the MENU mode, the system displays a plurality of menu items and icons, which correspond to and allow user selection of distinct program schedule information display formats, local cable system message boards and other on-line information 30 services. The MENU screen shown in Fig. 6 is a fullscreen display. In the embodiment shown in Fig. 6, there are four vertically selectable horizontal bars 61-64, which are accessed using the up and down direction arrows 43A on the remote controller 31 or 40. At the extreme left of each bar, an identifying icon 61A-64A is displayed, which identifies the information contained in that bar. In the embodiment of Fig. 6, the "TV GUIDE" icon 61A in the first bar corresponds to program schedule information from TV Guide® magazine, the "NOW 40 SHOWING" icon 62A in the second bar 62 corresponds to pay-per-view and premium service events, the "MSO Logo" icon 63A in the third bar 63 corresponds to Customer Service or local cable company information messages, and the circular icon 64A in the fourth bar 64 corresponds to other interactive services available to the user, or in the case of broadband networks, other venues, e.g., home shopping, banking or telephone use. As also shown in Figs. 6 and 6A, each bar also contains a textual description of its contents.

[0099] When the user first enters the MENU mode, the system defaults to selection of the program schedule bar. When a particular bar is selected, the textual description is removed and a plurality of icons or identifying windows are displayed adjacent the identifying icon. in Fig. 6. the program schedule bar 61 is selected. Using the up or down direction arrow key on the remote controller 40; the user selects a vertically adjacent bar Figs.

15-17 show, respectively, selection of the Pay-Per-View bar 62, the Customer Service or Messages bar 63 and the Interactive TV services bar 64.

[0100] An alternative MAIN MENU screen 215 is shown in Fig. 38. Certain selection screens accessible from the menu shown in Fig. 38 are shown in Fig. 38 and 38B. It has there onlice onlice the subsequence of the subsequenc

[0101] Once a particular bar in the MENU screen is selected, the user can select a particular icon from the plurality of horizontally selectable displayed icons 65A-56S by using the lett or right direction arrow and the EN-FER key on the remote controller 4D. Each icon contains a graphical symbol appearing in a background window of a particular color. When a particular is selected, it is offset from its background window and the color of the window changes. In Fig. 6, the grid icon 65A immediately adjacent the "TV GUIDE" icon in the first bar 61 is selected.

[0102] The function corresponding to the selectable enthries in the MAIN MENU screen will now be discussed with reference to Fig. 6. It will be appreciated by those of skill in the art that the same functionality applies in the categories shown in the MAIN MENU 215 shown in Fig. 38.

[0103] In the uppermost vertically selectable horizontal bar 61, the first grid icon 65A represents an "All Listings" mode in which the program schedule information is displayed in a grid listing, such as that shown in Fig. 18. Alternatively, a single column grid-like display could be used, as that shown in Fig. 25. In this format, the vertical y-axis identifies the channel number and service while the horizontal x-axis identifies the time. The screen display of Fig. 18 also contains in the upper lefthand corner a mode identifier 180, in this case the notation "All Listings," to remind the user of the current operating mode of the system. Directly underneath the mode display is a highlighted display 181 of the channel that the user was watching before entering the MENU mode. In the upper right-hand corner, a logo icon 182 appears in a window directly above a date/time identifier 183, which alternatively displays the current date and time

[0104] In the center of the screen display shown in Fig. 18 is a graphical Active Key Display (AKD) last which indicates to the user those keys on the remote of controller that are active for that particular mode of the program guide display system. For example, in the screen display of Fig. 18, the cursor can only move up, down or to the right. If the user were to depress the left direction arrow key on the remote controller at that point, the system would not carry out any function since the cursor can not move to the left. Thus, the left arrow key is not active so its image is not displayed on the AKD 1844. Similarly, since the system will only respond to a

depression of the up, down or right direction arrow keys and the ENTER key, they are the only key images displayed on the graphical AKD 184. The MODE key, though not displayed, is always active to change from one mode to another. When the user first enters the All Listings guide, the time listing begins by default at the half-hour immediately preceding the current time unless the current time is on the hour or half-hour, in which case the display begins with the particular hour or half-hour, and the channel listing begins at the last channel being viewed by the user before entering the MENU mode. For example, in Fig. 18, the current time is displayed as 7:30 p.m., the time listing begins at 7:00 p.m. and the channel listing begins with channel 4.

[0165] In the Ail Listings mode, a moveable highlighted of courself 86 is used to indicate the currently selected program to the user. The user manipulates cursor movement using the direction arrow keys on the remote controller 40. Furthermore, the entire information display pages upward if the cursor is placed at the bottom of the screen and the down direction arrow is depressed, and similarly pages to the left if the cursor is at the extreme right side of the display and the right direction arrow is depressed. In this way, the user can navigate through the entire program schedule.

[0106] The folder icon 65B immediately to the right of the All Listings icon in the top horizontal bar 61 of Fig. 6 identifies a "Category Listing" mode in which program schedule information is displayed and categorized by program content, as shown in Fig. 19. The particular listing shown in Fig. 19 includes the categories of Movies, Sports, News and Children 190A-190D. The database record stored for each listing contains a content-specific identifier so the microcontroller can search the database and categorize the information by content for purposes 35 of displaying it in the Category Listing mode. As shown in Fig. 19, the user can manipulate the cursor left or right to highlight any one of the categories which appear at the head of the listing. In Fig. 19, the "Movies" category 190A is selected. As shown, the user is given a display of all movies, prioritized by time and then alphabetically by title of show, beginning with the half-hour immediately preceding the current time unless the current time is on the hour or half-hour, in which case the display begins with the particular hour or half-hour. The screen display shown in Fig. 19 also includes a textual description of the current operating mode of the program schedule system, as well as the graphic AKD 184, similar to that used in connection with the All Listings mode.

[0107] As with the All Listings mode, if the user highlights a show which is currently airing, he can immediately tune to that show by depressing the ENFER key on the remote controller 40. If the highlighted show is one that will appear at future time, the user is again given the option of setting a REMINDER message.

[0108] The triangular icon 65C at the far right of the TV GUIDE bar 61 in the display of Fig. 6 identifies a "Channel Listing" mode in which the program schedule

information is categorized and displayed by channel, as shown in Fig. 20. The screen display shown in Fig. 20 again includes a lextual mode identifier 201, the graphic AKD 184, and the window including the logo icon 182 and alternating time/date display 183. At the head of the program listing is a list of swarpl concentric between

and alternating time/date display 183. At the head of the program listing is a list of several consecutive channels 202A-202C beginning with the last channel viewed by the user before entering the Channel Listing mode. The channel in the middle window 202B is highlighted and is the channel for which schedule information is dis-

channel in the middle window 2028 is highlighted and of is the channel for which schedule information is displayed. The display identifies those programs appearing on the highlighted channel beginning with the half-hour immediately preceding the current time unless the current time is on the hour or half-hour, in which case the 5 display begins with the particular hour or half-hour. The user can display further future listings by manipulating the cursor to the bottom of the screen and paging the display, as previously described. The user can also change the selected channel by manipulating the left or change the selected channel by manipulating the left or

to right direction arrow keys on the remote controller 40. When the user issues a charge-channel command in his manner, the next consecutive channel will be displayed in the highlighted window 2028 in the channel string at the head of the display, and schedule information for the newly selected channel will be displayed on the television receiver 27.

(0109) As with other modes, if a user wishes to tune to a highlighted program that is currently airing, he can do so by simply depressing the ENTER key on the remote controller 40, and if the user wishes to view a program that airs at a future time, the user is again given

the option of setting a REMINDER message.

[0110] In each of the FLIP, BROWSE and MENU modes, a lower case "i con appears at a number of soccasions in connection with certain program isstings, such as movies, such as the "i" 203 shown in Fig. 20. Any time this icon appears, the user can view additional programming information, generally comprising a toxical description of program content and/or other information in the content of the program is of the same sof cast members and the like, by depressing the "i key 48 on

the remote controller 40. An example of a display of such

additional information is shown in Fig. 21.

[0111] The second horizontal bar 62 appearing on the 15s crean in the MAIN MENU mode shown in Fig. 6 is the 15s crean in the MAIN MENU mode shown in Fig. 6 is the 15s cream in the MAIN MENU mode shown in Fig. 16 is the 15s cream in the MAIN MENU mode shown in Fig. 16 in the steadard is charged by the user, the television receiver displays information as shown in Fig. 15. The first theater-toket icon 150 that appears in this Home Theater bar identifies a format in which the Pay-Per-View events and premium service, as thought in the Pay-Per-View events and premium service, as they in Fig. 22. As with other modes, the user can manipulate the cursor to highlight and select any particular show. Also, the user can obtain additional methods.

bis lect any particular show. Also, the user can obtain additional information about the Pay-Per-View event or service by depressing the "i" key 48 on the remote controller 40. The Pay-Per-View menu screen display shown in

Fig. 22 also includes a video display section 220 in which short promotional clips of current and future events and services can be shown to the user while the user is viewing the Pay-Per-View scheduling information. The display of Fig. 22 is bit mapped such that the advertising clips may be shown in the lower left quadrant of the screen. The clips may be shown randomly be risk of the screen. The clips may be shown randomly be clips shown to the clips shown that the clips shown that the clips shown the cl

[0112] When a user highlights a Pay-Per-View event or service by manipulating the cursor to the desired event or service using the direction arrow keys on the remote controller 40, he can order the event or service by depressing the ENTER button on the remote controller, thus linking schedule, promotional and ordering functions. If the user selects a particular Pay-Per-View event or service in this manner, the programming schedule system will next present to the user a Pay-Per-View 20 ordering screen such as that shown in Fig. 23. The display includes a figure representing the cost of the event or service. The display also asks the user to choose from among a plurality of scheduled airing times 230A-230C. as well as whether the user would like to see a REMIND- 25 ER message prior to the start of the Pay-Per-View event or service. The user responds to these inquiries by using the direction keys on the remote controller 40 to manipulate the cursor to the proper response and then depressing the ENTER key. After the user has ordered a 30 Pay-Per-View event or service, the program schedule system will present the user with two ordering confirmation submenus, such as shown in Figs. 24 and 24A. In either of these submenus, the user can confirm or cancel the Pay-Per-View event or service.

[0113] If the user confirms the order, the microcontroller 16 stores the Pay-Per-View ordering information in a location in memory. The ordering information can then be transmitted to the cable operator by the microcontroller 16 either by phone line or on the cable line where the system has two-way communication or other such interactive capability. Alternatively, a computer at the cable operator location can interrogate the memory where the microcontroller stored the Pay-Per-Viev ordering information. At the appropriate time, the cable operator supplies the Pay-Per-View event or service and it is received by all users who have ordered the program. [0114] The second icon 151 in the Pay-Per-View bar of Fig. 15 identifies a specialized broadcast, cable or satellite programming service to which the user has access via the electronic program guide. In this mode, the electronic program guide application software acts to connect the user, through an appropriate data transmission link, to the programming service, at which point the user interacts with the service. Alternatively, the electronic program guide provides the navigation software. including the menus and scheduling information, for the particular programming service. Such a service could

be, for example, Your Choice TV ("YCTV"), a service offering reruns of highly rated broadcast and cable programs, in which case the icon may take a form suitable to identify YCTV. The programming available on YCTV is then supplied to the user via the programming guide system.

[0115] The last icon 152 appearing in the Pay-Per-View bar of Fig. 15 identifies a display format which lists all Premium Services offered by the cable operator, as shown in Fig. 26. In this mode, the user can select for impulse ordering any one of the premium services by manipulating the cursor using the direction arrow keys on the remote controller and depressing the ENTER kev. Similar to Pay-Per-View ordering, the system will present the user with a series of ordering displays and, if a service is ordered by the user, it will confirm the user's request using another other submenu. If confirmed, the microcontroller 16 will store the ordering information or transmit it directly to the cable operator. Once the order has been confirmed, the microcontroller can immediately allow the user access to the ordered premium service. In this manner, the user can order premium events or services on demand.

(0116) If, furing FLIP or BROWSE modes, a user severe a channel or schedule information for a service not subscribed to by the user, the microcontroller 16 causes an ordering submenu to appear instead of displaying a program signal along with the graphic overlay, as shown in Fig. 9. This submenu indicates to the user that she does not currently subscribe to the selected service, and then asks the user if she would like to order the service. If the user responds affirmatively, the program schedule system takes the user to the ordering submenu discussed above. In this manner, the user can order premium events or services on impulse.

shown in Fig. 6 is the "Messages" or "Customer Service" listing. As shown in Fig. 16, the first envelope icon 160 represents message information available from the cable operator. When the user selects the message icon, he is presented with a screen display of currently available messages, as shown in Fig. 27. The display shown in Fig. 27 includes cable system messages 270 and billing information 271. If the user selects the cable system messages option 270, she is presented with a message pertaining to the local cable operator, such as that shown in Fig. 28. If the user selects the billing status option 271 shown in Fig. 27, she is presented with a display of current billing information, such as that shown in Fig. 29. This information may include a history of purchases charged to the user, current balance information, pending orders, and, an indication of available credit, which can be an authorized debit limit previously arranged with the cable or other operator. Thus, a user could specify only a certain pre-set spending limit. Once the amount of charges from pay-per-view events reaches the limit, the microcontroller would not permit further ordering of events. An alternative messages menu is

shown in Fig. 28A.

[0118] The next icon 161 in the Customer Service information bar 63 of Fig. 16 identifies a Viewer Preference' mode, which allows the user to create or revise a number of program schedule system operating paramters. Once selected, this display presents the user with several preference options concerning certain operating parameters of the program schedule system, as well as the viewing of certain channels and/or certain contentspecific programming, for example, those shown in Fig.

[0119] The first option shown in Fig. 7 is the "Parental" option 70, which can also be expressed as a "Key Lock Access" option. Once this option is initially selected by the user, the system displays a "Key Lock Access" submenus such as that shown in Fig. 30.

[0120] The Key Lock Access menu shown in Fig. 30 allows the user to control access to individual channels and programs or events by requiring the user to enter an access code "Key," consisting of a user-specified four a

[0121] The first subject entry shown in Fig. 30 is the "Parental Guidance" category 301, once the user selects this category by manipulating the cursor to highlight the entry, the cursor can be then moved horizontally to an active window 302 which displays and selects one 35 the five letter rating items in the category. The letter items represent ratings of program content as follows: "V" for violence, "N" for nudity, "L" for language, "AS" for adult situations and "PD" for parental discretion. Once the user selects a particular item, such as "L", by moving 40 to the active window 302 using the right direction arrow key, depressing the ENTER key will indicate to the microcontroller 16 that a key lock access has been selected for programs rated with a "L" rating for violent or explicit language. The system indicates activation of a key lock access by displaying a key icon directly below the "L" category display. Once a key lock access is set, it can be deactivated by selecting the category letter and then depressing the ENTER key. This action causes the key icon to disappear. The user can change the rating category in the active window 302 by using the left or right direction arrow keys on the remote controller 40, images of which are displayed on the screen adjacent the active window as a reminder to the user. In this manner, the user can select other rating categories for setting a key lock access for any of the program content identifiers appearing in the Parental Guidance category. [0122] The key lock access code itself consists of a

four digit code, which the user can enter and modify at any time. To do so, the user highlights the fourth vertically selectable entry "Change Key Lock Access Code," 304 by manipulating the cursor to highlight it using the direction arrow keys on the remote controller. Once highlighted, the user enters a new four digit code or revises the then existing code and depresses the ENTER key. The microcontroller 16 then identifies the new four digit key lock access code and stores it in memory. The user can clear the key lock access code, as well as all other previously activated keys, by moving to the last entry in Fig. 30, "Clear Key Lock Access Code and All Keys,\* 305 which highlights the "OK" window, and then depressing the ENTER key. This action clears and deactivates all previously set keys, as well as the key lock access code.

[0123] The schedule information database record for each program contains a field that corresponds to the program content identifiers in the Parental Guidance category. During operation, the microcontroller checks this field in response to a user command to tune to or order a program, or to display its corresponding schedule information before carrying out the tuning, ordering or displaying function. If the parental guide identifier in the program schedule information database record matches any one of the activated parental guidance identifiers shown in Fig. 30, the user will be prompted to enter the four digit key lock access code before the system takes any further action. If the entered code matches the key lock access code previously entered and stored by the user as described above, the system will carry out the user request to tune to the program, to order it, or to display its corresponding schedule information. If the code is not recognized by the system, no further action will be taken and the user's request will be denied.

[0124] By manipulating the cursor using the direction arrow keys to highlight the second entry, "MPAA ratings," 308 the user can also set a key lock access for o programs based on their MPAA rating code, as also shown in Fig. 30.

[0125] As with the Parental Guidance category, once the MPAA rating category has been selected, the user can move horizontally within the category to the active window 306 to select one the five rating codes, i.e., "G" for general audiences, "PG" for parental guidance, "PG-13" for suggested parental guidance, no one under 13 admitted without an adult, "R" for restricted and "X" for x-rated. As with the Parental Guidance category, by selecting a particular rating --by using the left or right direction arrow keys until the particular rating code appears in the active window--and then depressing the ENTER key, the user sets a key lock access for the rating, in which case a key icon appears below the rating code. And, as with the Parental Guidance category, once a key lock access is set, the system will prompt the user to enter the four digit key lock access code anytime a request is made to tune to, order or display

schedule information for a particular program having a rating code which matches a rating code for which key lock access has been activated.

[0126] The Key Lock Access mode also includes a subject category 303 for controlling access to channels, which may be entitled, for example, "Channel Block" or "Channel Lock." As with the Parental Guidance 301 and MPAA 308 categories, the user navigates to the Channel Block category 303 by manipulating the cursor using the direction arrow keys on the remote controller and depressing the ENTER key. Once the Channel Block category 303 has been entered, the user can move horizontally to an active window 307, which in Fig. 30 indicates channel 2. Once the user highlights this window by manipulating the cursor using the direction arrow 15 keys on the remote controller 40, a key lock access can be set for the channel appearing in the active window. This is done, as with the other subject categories in the Key Lock Access mode, by depressing the ENTER key, which again causes a key icon to appear below the channel number in the active window. The user can move to the prior channel or to the next channel in sequence by depressing either the left or right direction arrow key on the remote controller 40. In this manner, the user can activate a key lock access for any available channel.

[0127] As with the Parental Guidance 301 and MPAA 308 categories, once a key lock access is set for a particular channel, the system will prompt the user to input the key lock access code prior to carrying out an instruotion to ture to or order that channel. If the input key lock access code matches the previously stored access code, the user's instruction is carried out. Otherwise, the user's instruction is entired out. Otherwise, the user's instruction is ignored. Thus, the user can control access to the adulo and video program content of any 35 available channel. In this instance, the microcontroller if will not allow audio or video program signals to pass to the VDG, but it will allow schedule information to appear for the channel.

[0128] An alternative method for effecting lockout of programs is accomplished using a "Lockout" screen, as shown in Fig. 39. in addition to limiting access to programs based on the Parental Guidance, MPAA and channel criteria, as discussed above, access may be limited on the basis of program title. Fig. 39 shows an alternative Lockout screen 250 that can be used to permit or limit access to programs based on program title, in addition to the aforementioned criteria. Other parameters also may be included, such as time of day, day of week, credit limit, and content category (e.g., talk shows).

[0129] To enter the Lockout screen 250 shown in Fig. 39, the user must enter a mutil-digit lockout code using the numeric digit keys 42 and the enter key 44 on the remote controller 4.0. The lockout code is set initially when the system is first used or installed. To set a lockout code in the first instance, the user accesses a Setup screen 260, such as that shown in Fig. 4.0. The Setup screen 260, such as that shown in Fig. 4.0. The Setup

screen 260 will automatically appear the first time the electronic program guide is installed and initialized. For access during normal operation of the electronic program guide, a suitable access path to the Setup screen 260 may be provided, such as from an appropriate icon in the MAIN MENU 215.

[0130] In the Setup screen 260 of Fig. 40, the user can navigate to the Lockout Code category 265 and eater a new lookout code using the appropriate navigation and selection keys on the remote controller 40. A suitable menu for inputting the lockout code is shown in Fig. 40A. Once enabled, the lockout code must be used to set or modify locks, to view a previously locked program, or to clear or change the lockout code. The memory location

5 of the stored lockout code also should be remotely accessible, such as by the local cable company, in case the user forgets the lockout code and it must be erased. (0131) Once the lockout code is entered and the Lockout screen 250 of Fig. 39 is displayed, navigation within 0 the screen is controlled by the direction keys 43A and 43B on the greate controller (41 Listense the State Controller).

43B on the remote controller 40. Using the up and down direction keys 43A to move the selection cursor, either the Movie Rating 251, Parental Guidance 252, Channel 253, Locked Program 254 or Lockout Code 255 category can be selected. The left and right direction keys 43B are then used to navigate inside the selected category. [0132] Clearing a previously set lockout code is accomplished by moving the selection cursor to the "Clear" entry 256 in the Lockout Code category 255 and depressing the enter key 44 on the remote controller 40. This causes the microcontroller to clear the lockout code stored in memory, as well as all locks previously set by the user. To change the current lockout code, the user navigates to the "Change" entry 257 in the Lockout Code category 255 and depresses the enter key 44 on the remote controller 40. The user is then prompted to enter a new lockout code, which is subsequently stored in memory by the microcontroller.

[0133] To set a lock in either the Movie Rating 251 or Parental Guidance 252 category, the user navigates to the selected entry in Fig. 39 by manipulating the selection cursor using the direction keys 43A and 43B on the remote controller 40, and then depresses a lockout key on the remote controller, such as the padlock key 45A shown in Fig. 4. The microcontroller will appropriately modify the display to indicate that a lock has been set, for example, by changing the color of the text or the background in the selected entry window, or by displaying an appropriate icon next to the text in the selected entry window. In Fig. 39, a padlock icon 258 appears in the window of the "PG" entry in the Movie Rating category 251. Toggling the lockout key while the selection cursor is positioned on a selected entry will alternately enable and disable the lockout function for that entry. [0134] Similarly, to set a lock for a particular channel,

5 [0134] Similarly, to set a lock for a particular channel, the user selects the channel using the selection cursor and then depresses the lockout key. In Fig. 39, the channel "4 KCNC" entry in the Channel category 253 has been locked, which is indicated by the inverse video and padlock icon appearing in the window.

[0135] Program locks also may be set by title, which can be effected in several ways. For example, when the above-described FLIP or BROWSE mode of the electronic program guide is enabled, thereby causing the title of a program to be displayed along with other program schedule information in a window superimposed on the actual program signal then being received, the user can limit access to the program corresponding to 10 the displayed program information by depressing the lockout key 45A on the remote controller 40. The user also may limit access to the currently tuned program by depressing the lockout key 45A on the remote controller 40 while viewing the program, regardless whether the 15 FLIP or BROWSE modes are enabled. In this instance, the microcontroller first removes the program signal from the display and then accesses the schedule information database record for the program then appearing and sets an appropriate flag to indicate the program has 20 been locked. Also, when viewing program schedule information in the grid or category listings, as discussed above and shown, for example, in Figs. 18-20, the user also can tag a program for lockout by highlighting it with the selection cursor and then depressing the lockout key 25 45A on the remote controller 40.

[0136] In each of these instances, the microcontroller then stores the program title in a lockout title list stored in memory along with any other titles that previously have been locked out by the user. Individual items in the lockout title list are displayed in alphabetical order in the "Locked Program" window 259 shown in Fig. 39, and the user may scroll through the list by positioning the selection cursor on the Locked Program window 259 using the up and down direction keys 43A on the remote 35 controller in Fig. 40 and then using the left and right direction keys 43B to scroll through the list one item at a time. In order to save memory space, alternatively, the microcontroller may be programmed to set a flag or otherwise mark the particular database record containing the program schedule information for the program that is to be locked out, and to thereafter access the database to retrieve the title information when it is to be displayed, such as when the viewer is reviewing the lockout

title ist in the Locked Program window 259.

[0137] Once an individual title has been locked out, the microcontroller can be programmed optionally to display an appropriate lockout icon, such as a padlock, whenever program schedule information for the locked program is to be displayed, such as in the window overlay of the FLIP or BROWSE mode, or in the various did and category displays available in the MAIN MENU displays. The system also may display an appropriate text message if someone thies to access the program signal of a previously-locked program. Of course, once a program is ofceder, in all instances the microcontroller prevents access to the actual program signal (including both the audio and video portions of the program signal)

until an appropriate code is entered or the lockout is removed.

10138] Several methods can be used to block programs at their time of airing. For example, in the case of the Movie Rating, Parental Guidance and Channel categories, the schedule information database record for each program is provided with a field that corresponds to the rating, program content identifier or channel appearing, respectively, in the Movie Rating 25-parental Guidance 256 and Channel 253 category of the Lockout screen 250 shown in Fig. 39.

[0139] During operation, the microcontroller checks the appropriate field in the database record in response to a user command to tune to or order a program before carrying out the tuning or ordering function. Additionally, the lockout code also may be used to restrict access to program schedule information. In this instance, the microcontroller also would check the appropriate field in the schedule information database record before displaying schedule information for a program.

[0140] If the movie rating, parental guidance or channel identifier in the program schedule information database record matches any one of the locked-out entries indicated in the Lockout screen 250, a Lockout Verify screen 300 is displayed in overlaying relationship with the video signal then being displayed on the television receiver, as shown in Fig. 41. The user will be prompted to enter the previously set lockout code before the system takes any further action. As an added security measure, asterisks will be displayed as the user enters the lockout code. If the entered code matches the lockout code previously entered and stored by the user as described above, the system will carry out the user request to tune to or order the program, or to display its corresponding schedule information. If the code is not recognized by the system, no further action will be taken and the user's request will be denied. In this case, the Lockout Verify screen 300 will remain displayed on the television receiver waiting for a correct code to be entered. If no action is taken by the user, the Lockout Verify screen 300 will be removed after a predetermined timeout period, such as one or two minutes.

[0141] Similarly, in the case of lockout by title, the microcontroller also could check the title field in the schedtion of the controller also could check the scheduler of the first of program titles for which the user previously set a lock. If, as described above, the microcontroller does not maintain a list of the actual titles of programs locked by title, a suitable identifier can be set in a field in the database record to indicate that a program has been locked by title when the user first sets the lock, and, thereafter, the microcontroller could check that field in response to a user request to tune to or order a program, or display schedule information.

55 [0142] An alternative method for effecting lockout involves the use of a portion of the real-time program signal being received by the television receiver. With this method, codes corresponding to a program's rating, pa-

rental guidance category, title or channel are inserted into and transmitted ating with the program signal, such as in the vertical or horizontal blanking intervals, or on raster scan lines that are not visible on the television receiver. When the program signal is received, these codes are stripped from the program signal and stored in memory. Methods and apparatus for the insertion transmission and reception of digital codes carried on a program signal are known in the arc known in the arc from the signal of the

[0143] After the transmitted codes have been separated from the program signal and stored in memory, the microcontroller can compare them with the lockout criteria set by the user in the Lockout screen and take appropriate action, as described above.

[0144] The Setup screen 260 shown in Fig. 40 also 15 contains a Purchase Code category 270, which allows the user to set a numeric purchase code that must be entered before any premium channels or pay-per-view programs can be ordered. The Setup screen 260 shown in Fig. 40 includes entries for setting a new purchase 20 code and for clearing or changing a previously set password. Appropriate menus for setting, confirming, clearing or changing the purchase code are shown in Figs. 40B through 40E. Once a user sets a purchase code, the microcontroller thereafter will display a Purchase Code Verify screen in response to a user request to tune to or order a premium services channel or pay-per-view program. The Purchase Code Verify screen works in a manner similar to the Lockout Verify screen 300 in that the user is prompted to enter the previously set pur- 30 chase code password before the microcontroller will tune to or order the requested program. If the correct purchase code is not entered, the microcontroller will take no further action and the Purchase Code Verify screen will remain displayed waiting for input of the correct code. If no action is taken within a predetermined time-out period, the Purchase Code Verify screen will be removed

[0.145] The next option shown in Fig. 7 is the Channel Preference or "Favorite Channel" isl option 71. By high-lighting this icon and depressing the ENTER key on the remote controller 40, the user is presented with a submenu on the screen such as that shown in Fig. 8.

[0.146] In inormal operation, the program guide system presents channels to the user in numerical order in response to an up or down change-channel command issued by the user using one of the direction arrow keys on the remote controller. The channel number presentation sequence includes all channels offered by the cable company in the order of which they are modulated onto the channel by the operation.

[0147] The program guide system also provides the capability of selecting from among several user-defined channel presentation sequences, which are activated using one of the three 'check mark' icon keys 48A, 48B or 48C on the remote controller 46 shown in Fig. 4. Each of these keys represents a preferred particular list of channels winch a particular user selects and which channels winch a particular user selects and which we have the control of the control microcontroller stores in memory as a "Channel Preference" list, as discussed in detail below. To activate one of these preferred channel lists, the user depresses the corresponding check-mark icon key, in which case the corresponding check-mark icon key, in which case the microcontroller may display the chosen icon on the screen in the graphic overlays and full screen displays to remind the user that a particular channel preference list is being used by the system. Once a preference list is activated, the system will limit the tuning of the television receiver and the display of schedule information only to those channels that are designated in the activated viewer preference list.

[0148]. To revise the content and/or sequential order of the channels in the Channel Preference list, the variety of the channels in the Channel Preference list, the variety of the programming guide system. To enter the MENU mode from the FLIP mode, the user twice depresses the MODE key 38 when using the remote controller 31 of Fig. 3. To enter the MENU mode when using the alternative embodiment of the remote controller 40 of Fig. 4, the user simply depresses the MENU content of the Variety 47B.

[0149] When first entered, the MENU mode has a screen display such as shown in Fig. 6. To select the submenu for editing the Channel Preference list, the user first selects the third horizontal bar 63, which can be titled, for example, "Messages" or "Customer Service," by manipulating the cursor using the down direction arrow key, as shown in Fig. 7. The screen of Fig. 6A is thereby displayed. The user then selects the second icon 161 appearing in that bar, indicated with a check mark, which corresponds to a "Viewer Preference" mode, by highlighting the icon using the direction arrow kevs and again depressing the ENTER key. This action will cause the microcontroller 16 to display a Viewer preference submenu such as that shown in Fig. 7. By selecting the Channel Preference or "Favorite Channel" entry 71, the user enters the Channel Preference submenu, shown in Fig. 8. If the user has not already done so, he would then depress the particular check-mark icon key on the remote controller 40 of Fig.4 to create or revise the particular channel preference list.

[0150] In the Channel Preference menu shown in Fig. 8, a list 81 of all channels available on the particular cabels system is displayed on the left side of the television receiver screen, labeled "Choices" in Fig. 8, and the viewer's preferred list 81, designated "Selected" in Fig. 8, is displayed on the right side. If a particular code, sons an END or "1" symbol appears in the first (uppermans) position 82 of the viewer preference list 81, the system displays information for all channels in numerical order in all modes of operation. This is the default mode of the system.

(0151) By selecting channels in sequence from the available list 80 and placing them in the desired order in the preference list 81, the user can select a subset of channels and/or rearrange the default sequence in response to a channel up or channel down command from the user. This is accomplished by highlighting a Channel in the available list 80 using the up and down direction arrow keys on the remote controller 40 and depressing the ENTER key 44, which stores the entry temporarily in a buffer.

[0152] The microcontroller 16 stores a list of all channels previously entered in the viewer preference list 81. As a particular channel is highlighted by the user when navigating through the available channel list 80 displayed on the left side of the television screen, a window 84 appears adjacent to the particular channel highlight- 10 ed by the user. If the particular channel already appears in the viewer preference list 81, the system displays a "DELETE" message in the window 84 as a reminder that the channel was previously selected from the available channel list 80 and can only be deleted from the list 81, which is accomplished by depressing the ENTER key 44. If the particular highlighted channel in the list 80 was not previously selected, the system displays a "SE-LECT" message in the window 84 as a reminder that the particular channel will be selected for addition to the viewer preference list 81 if the user depresses the EN-TER key 44. The microcontroller 16 inserts a selected channel at the bottom of the list 81. In this manner, the user can select or delete channels from the viewer preference list in any desired order.

[0153] The available channel list 80 may also be provided with categorical entries 83, such as movies, news, sports or children's shows. The user may also highlight any of these entries and put them into the viewer preference list 81. If the user does include a category in his oviewer preference list 81, when the user issues channel up or down commands, the system will display, in sequence, first the user's selected preferred channels in unmerical order and then all channels having a program whose content corresponds to the selected category or 35 categories at the time.

[0154] Once the user has revised the channel preference list 81 in the described manner, the microcontroller 16 will follow the stored user-specified channel sequence in response to a change-channel command made by the user employing one of the direction arrow keys. To activate the viewer preference list, the user depresses one of the three check-mark icon keys 48A, 48B or 48C on the top of the remote controller shown in Fig. 4. The viewer preference list can be used to selectively limit tuning of the television receiver or display of schedule information in any of the operating modes of the electronic program guide. In the present embodiment, once a preference list is activated, the system will limit the tuning of the television receiver and the display of schedule information in the FLIP, and BROWSE modes, as well as in the grid category and channel listings in the MENU mode, only to those channels designated in the activated viewer preference list. The tuner can not be tuned to, and no corresponding schedule information can be displayed for, any channel not entered in the viewer preference list when it is activated. In this regard. it should be noted that setting a key lock access in the

Parental Guidance 301, MPAA 308 or Channel Block 303 categories produces a different result than when using other display criteria, such as the Channel Preference List of preferred channels discussed above. Thus, while a key look access will prevent audio and video program information, but not schedule information, from being displayed or ordered absent entry of an authorization code, if a particular channel is included in the Channel Preference list and also has a key lock access activated in the Channel Block category 303 of the Key Lock Access mode, that channel or its corresponding schedule information will not be displayed at any time.

[0155] To deactivate a previously selected viewer preference list, the user toggles the appropriate checkmark korn key on the remote controller 40 of Fig. 4. Once deactivated, the system defaults to displaying and tuning all available channels, as well as displaying schedule information for all available channels.

[0156] Alternatively, the viewer preference list 81, if 20 activated, can be used to control tuning and display of 30 schedule information only in selected modes, such as only in the FLIP mode, thus allowing the user to tune and view corresponding schedule information only for those channels entered in the preference list 81 in the FLIP mode, while viewing all channels and corresponding schedule information in all other modes.

(0157) In this latter configuration, as well as in the instance where no channel preference list is activated and the system is in default mode, if a channel appears in of the viewer preference list of that corresponds to a service not subscribed to by the user, the microcontroller 16 causes an ordering submenu to appear instead of displaying a program signal along with the graphic overlay, as shown in Fig. 9. This submenu indicates to the user to that he does not currently subscribe to the selected service, and then asks the user if he would like to order the service. If the user responsal sufficiency is the program schedule system takes the user or another ordering submenu confirm the user's request, as with impulse or-

[0158] The program guide also may be configured with a Locator screen 201, as shown in Fig. 37, which aids the viewer in channel selection and definition of a favorite channel list. The Locator screen 201 displays all available channel numbers grouped according to the source of the program information appearing on any particular channel at any particular time, e.g., broadcast, cablecast, pay-per-view, near video on demand, satellite, or other source of program material. Thus, the Locator screen 101 can be used to locate any particular channel or service because the groupings provide a quick and efficient method for scrolling through the list of available channels. The channel numbers also may be grouped according to other criteria, such as program category, program content, program rating or other content-based standard, time of availability, numerical order, or other logical grouping

[0159] In the example shown in Fig. 37, the user nav-

igates within the Locator screen 201 using the direction keys 43A and 43B on the remote controller 40. The right and left direction keys 43B move the selection cursor within the category rows, while the up and down direction keys 43A are used to select a particular category. From the Locator screen 201, any particular channel can be selected for viewing by positioning the selection cursor on the desired channel and depressing either the enter key 44 or an optional tune key (not shown) on the remote controller 40.

[0160] In addition to aiding in channel selection, the Locator screen 201 also provides the user with the ability to conveniently define favorite channel lists. To do so, the user first moves the selection cursor to the desired channel by using the direction keys 43A and 43B or numeric digit keys 420 in the remote controller 40, and then depresses a favorite channel key 46A provided on the remote controller 40, which causes the display to change in some manner or characteristic as an indication that the channel has been selected as a favorite channel, such as by changing the color of the channel identification to to the text background, by displaying an appropriate icon or by some other appropriate identification store when the remote controller 40 shown in Fig. 4, the power was the controller 40 shown in

[0161] Also, if multiple favorite channel lists are being used, the user would depress the appropriate favorite channel key on the remote controller to select a particular list before depressing the favorite channel key. For 30 example, as discussed above, the remote controller 40 shown in Fig. 4, has three color-coded check-mark favorite channel keys 48A, 48B and 48C, which provide for at least three individual favorite channel lists for three individual users. Different identification characteristics 35 could be displayed on the Locator screen 201 to indicate that a particular favorite channel list is selected. For example, the icon or image used to enable a favorite channel list on the remote controller, such as the check mark kev 48A used on the remote controller 40 shown in Fig. 4, could be displayed on the Locator screen 201, as well as other screens of the program guide, when a favorite channel list is enabled. Alternatively, the color of the displayed text or background could be changed to match the color of the selected favorite channel key.

[0162] The Locator screen 201 may be accessed wis several paths. For example, it may be included as a virtual channel that is conveniently positioned in the channel-luning sequence, such as between the highest and lowest available channel numbers — for example, a virtual channel to. To the user, such a virtual channel appears to be a conventional channel. However, it requires no additional bandwidth as a carrier. For example, it can be digitally produced at the subscriber station or included in an appropriate blanking interval in existing bandwidth requencies. In this manner, the virtual channel is accessible either by entering the corresponding channel unmber using the numeric digit keys 42 on the remote

controller, or by using the up and down direction keys 43A to wrap around from the highest to the lowest channel number, or vice versa. As shown in Fig. 38, it also may be desirable to provide a suitable identifier, such as inco nor lest message 210, in the MAIN MENU display 215, from which the user could access the Locator screen 201 simply by highlighting the identifier 210 with the selection cursor and depressing the enter key 44 on the remote controller 40. Alternatively, the remote controller and be provided with a key corresponding to the Locator screen 201 which would cause the microcontroller to display the Locator screen 201 which would cause the microcontroller to display the Locator screen 201 which would cause the microcontroller to display the Locator screen 201 when the user depressed it.

[0163] In addition to Channel Preference or Favorite S Channel keys, the remote controller 40 can also be supplied with a number of user-activated category preference icon keys, e.g., movies, sports, or children's programming. The system can be adapted to present to the user only those programs meeting particular preference of category when it is activated by the user. As with the Channel Preference icons, the microcontroller may dishard to the contraction of the c

Channel Preference icons, the microcontroller may display the icon corresponding to the activated preference category to remind the user of the currently activated mode of system operation. [0164] The question mark icon 162 at the far right of

the third horizontal bar in the menu of Fig. 16 identifies a program guide system "Help" mode in which information explaining the operation of the system is displayed for the user. Again, by manipulating the cursor using the appropriate keys on the remote controller, the user can select this mode. Once selected, the next submenual phearing in the Help mode asks the user to identify the particular portion of the system about which the user would like to view Help information.

[0166] The icons appearing in the last horizontal bar of the MENU mode identify certain interactive and/or other types of information services which the programming system, acting as a gateway, makes available to the user as shown in Fig. 17.8 pmanipulating the cursor, the user can select any one of the identified services, as shown in Fig. 3.1-35.

[016]. For example, if the user initially selects the "X"PRESS" icon appearing in the last horizontal bar, he is presented with a submenu such as that shown in Fig. 51. Using the direction arrow and enter keys on the remote controller, the user selects one of the three entries appearing in the display of Fig. 31. Once a particular entry is selected, the electronic program guide connects the user to the selected service and passes control to the particular service application software, as shown in Figs. 32-35.

(0167) Alternatively, the remote controller 40 can be supplied with a plurality of content-specific keys corresponding to a plurality of content-specific categories of 5 programming-e, a. Sports key, News key, More key, etc. When the user depresses a content-specific key, a content-specific mode is mitiated. In Fig. 4, the remote controller is equipped with a Sports key 49 if the user

depresses the Sports key 49, the microcontroller will limit the display of programs and/or program shedule information to those that are sports-related. The microcontroller will block all other programming or schedule information from appearing on the television receiver. The microcontroller can be adapted to distinguish programs and schedule information that are sports-related by examining an appropriate code associated with the program or schedule information that

[0168] As discussed above, coding can be accomplished using any number of methods, such as by including an appropriate code in the vertical blanking interval of the program signal, or in an appropriate memory location in the database record of the program schedule information, or if the schedule information is 15 being received on a broadband network, by including it in an appropriate blanking interval. The user activates a content-specific mode by depressing the appropriate content-specific key in any mode of operation of the electronic programming guide, including the aforede- 20 scribed FLIP, BROWSE or MAIN MENU modes, as well as when no schedule information is being displayed and only a program signal is visible on the television receiver. Once a content-specific mode is requested by the user, the microcontroller immediately and directly ena- 25 bles the content-specific programming criteria, and maintains it for all operating modes of the guide until disabled, which can be accomplished, for example, by toggling the Sports key 49.

[0169] Instead of a dedicated content-specific key, such as sports key 49, the system may be configured with a single, generic content-specific key, which, when activated, would cause the microcontroller to display a content-specific categories available to the user. The user then sould highlight a particular category by manipulating the selection cursor using the direction arrow keys on the remote controller and select tip depressing the ENTER or OK key 44. As an alternative to using a content-specific key on the remote controller access to the content-specific key on the remote controller screen of the electronic guide, such as in the LOCATOR, SETUP or MAIN MENU screen.

[0170] In addition to blocking all non-selected conetent-specific programming when a particular contentspecific category has been selected, the microcontroller
can be programmed to enable all added-value programming or services that are specially related to the selected content-specific category. For example, if the user
activates a Sports content-specific mode, the microcontroller, in addition to allowing only sports programming
to be displayed, will proactively seek out and enable all
sports related added-value services, such as related as
sports related added-value services, such as related is
sports related added-value services. Such as related
sports programs, un-to-date soores while a game
is in progress, team schedules replays of prior games
of the selected teams or players, incider or sourcept purpor

chasing, etc. Thus, the information available from the programming or service can be integrated into the environment of the electronic program guide. Rather than simply passing control to another service as described above, in this manner the electronic program guide would function as a system integrator or interface to combine the available adder-duale information into a package within the electronic guide environment, thus essentially creating a series of modular electronic program applications corresponding to a variety of available content-specific categories.

[0171] The Setup screen shown in Fig. 40 also includes a Text Location category 275, which contains the textual entries "Bottom of Screen" and "Top of Screen." By navigating to the Text Location category 275 using the up and down direction keys 43A on the remote controller 40, and to either the "Top" or "Bottom" entries in that category using the left and right direction keys 43B on the remote controller, and then depressing the enter or select key 44, the user can control the position of the overlay windows used to display information in various operating modes of the electronic program guide. The Setup screen of Fig. 40 provides the user with two positional choices: the top or bottom of the screen. Depending on the modes of operation of the program guide, it may be desirable to provide the user with more positional choices in viewing area of the television receiver, or to provide the user with the ability to choose a different position for information displayed different operating modes.

[0172] One of the novel features of the disclosed invention is the textift system. The preferred embodiment of the text fit system includes an interactive computer program used to edit the program listings data before it is transmitted to the user and stored in memory. The interactive system operates as follows: unedited (or partially edited) program listings information is loaded into data a processor. The data includes program schedule times, duration, category, as well as additional descriptive information dependent on the type of program. For example, for movies the data includes the MPAA rating, year of the movie, whether it is in black and white, and a list of starring actors and actresses.

Use the data which includes television program titles as well as movie titles, sporting events and titles for other special events. Based on the duration of the program, the data processor first analyzes the Istings data to determine what grid size listings are needed for each title. Thus, a two hour movie could require four different edited titles to fit into each of the four different size grid cells (30, 60, 90, 120 minutes). The data processor than determines how much space is required to display the title based on its character length. If the title is to be displayed the program schedule grid using a proportional font and character to character kerning, the data processor may also account for these factors in determining the space required to display a title. The determination

would than be based on the number of pixels required for the particular combination of characters in the title. The amount of space available for display of a title depends on the size of the grid cell and the space required for display of icons, when activated.

[0174] If the data processor determines that a full title requires for much space to fit into one or more grid cells, the title is then presented to the editor using a suitable display device connected to the data processor, such as a CHT. The editor is then quered to alter the title so that 10 it will fit in the allotted space. If the title must be edited for more than one cell size, the editor is queried to edit each of these separately. In the preferred embodiment of the interactive program, the editor is given in real time whether the edited title will fit in the designated grid 15.

[0175] In the preferred embodiment, two lines of text are displayed in each grid cell of the program listings. The title, as edited, appears on the first line, and if necessary, continues onto the second line. The decision to awrap-around to the second line is based on whether neatural breaks exist in the title such as spaces between words, commas, periods, hyphens, etc. These are standard techniques used in word processing software routines. The editor may also be queried to edit a title in the situation where the full title will fin on the allotted two lines, but a hyphen is required because there are no natural breaks in the title.

[0176] Prior to querying the editor to shorten a title, the data processor compares the title with a stored inbrary of shortened titles to determine if the title had previously been shortened while editing another listings database. Each time changes are made by the editor to a title, the shortened title is added to the library. It is apparent that the process of building a library of shortened strength of the process of building a library of shortened of 1717. A flow chart illustrating the process by which

[0177] A flow chart illustrating the process by which the text fit system operates is shown in Fig. 42. The chart illustrates the operation of editing a listing for display in a program grid for a single platform, but operation is the same for all platforms.

[0178] Text editing may be necessary in other situations besides that where multiple size grid cells are used for display of the same title. For example, the disclosed program guide may run on several different platforms. with each one having different constraints and grid cell space availability. Some may not display the text in proportional fonts and some may have other limitations reducing the available space. Thus, in the preferred embodiment the interactive program would request edits for all platforms for which they required at the same time. In addition, editing of text may be required for display modes other than a grid of program listings. For example, in the "Listings by Channel" display of fig. 20, programs are listed on an entire, fixed-length line, but the length of the line may vary from platform to platform, so that the text fit system may be employed for the purpose of editing listings for the different platforms in this display

mode as well. The space available for the display of text will also depend on how much space is reserved for icon display. The same process as that shown in fig. 42 would apply, except that there would be no need to determine what grid sizes are needed because a fixed length line is used for display rather than multiple sized grid cells. [0179] I till be apparent to those of skill in the art that the disclosed text fit system has applications beyond fast of tille editing atone. The system may be easily modified to provide editing of messages, "i" screen storylines, pary-perview promotional copy, and similar text messages so that they will fit into the designated space available for display of the text. In fact, the system may be used to edit any text for display in the disclosed program schedule system.

[0180] The computer program for the microcontroller 16 may also include a schedule for the display of varying background views upon which the program schedule information is overlaid either partially or in a full screen display. The background views may be stored as bit maps in memory or in another storage medium, such as an optical storage device. For example, the microcontroller 16 may be programmed to issue a command to the VDG every morning at 6:00 AM to display a sunrise in the background. The background may then be changed accordingly throughout the day to, for example, a blue sky or a nighttime view. It also may vary, e. g., by time of day, day of week, month, year or season. The mood background also could change depending on the particular category of programming that the user is watching or to which selected schedule information pertains. The mood background also may be adapted to display scenes that reflect the particular viewing area in which the user is situated, like the Rocky Mountains, or Mt. Rainier, etc. It also may be possible to display standard scenes, such as an ocean or forest scene. Moreover, the audio background also could be adjusted to relate to the particular mood background then being displayed. In addition, different background views may be used for holidays and special events, such as Christmas, Fourth of July, Superbowl Sunday, etc. The purpose of the background views is to help ease the monotony of viewing program listings. The microcontroller 16 could be adapted automatically to coordinate the display of the mood background. The user also could be given the ability to choose from among various mood background displays by adapting the microcontroller to display an appropriate mood option menu that lists the mood background options available to the user and allows the user to select one or more by manipulating the selection cursor. Access to such a mood option menu

5 [0181] Additionally, the electronic program guide could be configured to store a unique digital identifier for each program along with its schedule information and later use the identifier - e.g., by transmitting it - to

such as the LOCATOR or SETUP screen.

could be achieved by supplying an appropriate identifier,

textual or visual, in an appropriate menu of the system,

indicate to a recording or storage device, such as a video recorder, that the user wishes to record the program. The program guide could also use the identifier to automatically control operation of the video recorder. The electronic program guide could also be configured to 5 use other stored schedule information for this purpose. [0182] The form and content of a particular computer program to implement the invention disclosed herein will be readily apparent to those skilled in the art of video system programming and graphic display. A flow chart 10 4. The system defined in Claim 3, wherein: showing the operation logic of the system is shown in Fig. 36. It will also be appreciated by those skilled in the art that there can be departure from the specific embodiment of the invention described herein without departing from the true scope of the claims appended hereto. 15

#### Claims

- 1. An electronic program schedule system for provid- 20 ing a user with an opportunity to view multiple air times for a program, comprising:
  - means for providing program schedule information including a plurality of air times for at 25 least one program;
  - means for receiving the program schedule information with an electronic program schedule
  - means for providing the user with an opportu- 30 nity to select the at least one program: and means for simultaneously displaying the plurality of air times of the selected at least one program with the electronic program schedule system
- 2. The system defined in Claim 1, wherein:
  - the means for providing program schedule information including a plurality of air times for at 40 least one program comprises means for providing program schedule information including a plurality of air times for at least one pay-perview program; and
  - the means for simultaneously displaying the 45 plurality of air times with the electronic program schedule system comprises means for simultaneously displaying the plurality of air times for the at least one pay-per-view program with the electronic program schedule system.
- 3. An electronic program schedule system for providing a user with an opportunity to select a particular air time of a program to perform a function associated with the program, comprising:
  - a video display generator:
  - a remote controller, and

a microcontroller programmed to (1) direct the video display generator to simultaneously display multiple air times for a program, (2) provide the user with an opportunity to select at least one of the multiple air times for the program with the remote controller; and (3) perform the function associated with the selected at least one of the multiple air times.

the program is a pay-per-view program; and the microcontroller is further programmed to order the pay-per-view program.

- 5. An electronic program schedule system for providing a user with an opportunity to view multiple air times for a program, comprising:
  - a receiver configured to receive program schedule information including a plurality of air times for at least one program;
    - a video display generator. a remote controller; and
    - a microcontroller programmed to (1) provide the user with an opportunity to select the at least one program with the remote controller. and (2) to direct the video display generator to simultaneously display the plurality of air times of the selected at least one program.
- 6. The system defined in Claim 5, wherein:
  - the program schedule information includes a plurality of air times for at least one pay-perview program; and
  - the microcontroller is programmed to direct the video display generator to simultaneously display the plurality of air times for the at least one pay-per-view program.
- 7. A method for use in an electronic program schedule system comprising:
  - receiving program schedule information including a plurality of air times for at least one program:
    - providing a user with an opportunity to select the at least one program; and
    - simultaneously displaying the plurality of air times for the selected at least one program.
- 8. The method defined in Claim 7, wherein:
- receiving program schedule information including a plurality of air times for at least one program comprises receiving program schedule information including a plurality of air times for

50

at least one pay-per-view program; providing a user with an opportunity to select the at least one program comprises providing a user with an opportunity to select the at least one pay-per-view program; and at least one pay-per-view program; and simultaneously displaying the plurality of air times for the selected at least one program comprises simultaneously displaying the plurality of air times for the selected at least one pay-per-view program.

 An electronic program schedule information including a plurality of air times for at least one program; means for providing a user with an opportunity to select the at least one program; and

means for simultaneously displaying the plurality of air times for the selected at least one program.

10. The system defined in Claim 9, wherein:

the means for receiving program schedule information including a plurality of air times for at least one program comprises means for receiving program schedule information including a plurality of air times for at least one pay-perview program;

the means for providing a user with an opportunity to select the at least one program comprises means for providing a user with an opportunity to select the at least one pay-per-view program; and

the means for simultaneously displaying the plurality of air times for the selected at least one program comprises means for simultaneously 35 displaying the plurality of air times for the selected at least one pay-per-view program.

 An electronic program schedule system comprising:

> a receiver configured to receive program schedule information including a plurality of air times for at least one program; a remote controller;

a video display controller, and a microcontroller programmed to (1) provide a user with an opportunity to select the at least one program with the remote controller, and (2) direct the video display generator to simultaneously displaying the plurality of air times for the selected at least one program.

12. The system defined in Claim 11, wherein:

the program schedule information includes a plurality of air times for at least one pay-perview program; and the microcontroller is programmed to (1) provide a user with an opportunity to select the atleast one pay-per-view program, and (2) direct the video display generator to simultaneously display the plurality of air times for the selected at least one pay-per-view program.

A method for providing a user with an opportunity to select a particular air time of a program to perform a function associated with the program, comprising:

providing the user with an opportunity to simultaneously view multiple air times for a program; providing the user with an opportunity to select at least one of the multiple air times for the program; and

performing the function associated with the selected at least one of the multiple air times.

20 14. The method defined in Claim 13, wherein:

providing the user with an opportunity to simultaneously view multiple air times for a program comprises providing the user with an opportunity to simultaneously view multiple air times for a pay-per-view program;

providing the user with an opportunity to select at least one of the multiple air times for program comprises providing the user with an opportunity to select at least one of the multiple air times for the pay-per-view program; and performing the function associated with the selected at least one of the multiple air times comprises ordering the pay-per-view program.

 A method for providing a user with an opportunity to view multiple air times for a program, comprising:

> providing program schedule information including a plurality of air times for at least one program;

> receiving the program schedule information with an electronic program schedule system; providing the user with an opportunity to select the at least one program; and

simultaneously displaying the plurality of air times of the selected at least one program with the electronic program schedule system.

50 16. The method defined in Claim 15, wherein:

providing program schedule information including a plurality of air times for at least one program comprises providing program schedule information including a plurality of air times for at least one pay-per-view program; and simultaneously displaying the plurality of air times with the electronic program schedule systems.

45

20

40

45

tem comprises simultaneously displaying the plurality of air times for the at least one pay-perview program with the electronic program schedule system.

17. An electronic program schedule system for providing a user with an opportunity to select a particular air time of a program to perform a function associated with the program, comprising:

> means for providing the user with an opportunity to simultaneously view multiple air times for a program;

means for providing the user with an opportunity to select at least one of the multiple air 15 times for the program; and

means for performing the function associated with the selected at least one of the multiple air times.


18. The system defined in Claim 17, wherein:


the means for providing the user with an opportunity to simultaneously view multiple air times for a program comprises means for providing 25 the user with an opportunity to simultaneously view multiple air times for a pay-per-view program:


the means for providing the user with an opportunity to select at least one of the multiple air times for the program comprises means for providing the user with an opportunity to select at least one of the multiple air times for the payper-view program; and


the means for performing the function associated with the selected at least one of the multiple air times comprises means for ordering the pay-per-view program.


QF.














FIG.6A




FIG.7




FIG.8





FIG.9

Premium Services	Enter ▽	MSO LOGO 5:03pm
HBO Home Box Office \$10.40/Month		
SHO Showtime \$9.95/Month		
DIS The Disney Channel \$9.95/Month		
TMC The Movie Channel \$1.50/Month		
MAX Cinemax \$9.95/Month		
PLA Playboy at Night \$4.95/Evening(5:00pm to 3:00am)		
ACT Action \$5.95/Day(II:OOpm to 3:OOpm)		
Movie, special events, and family programming!		
You are not a Subscriber Press Enter o Subscribe!		

FIG.10






FIG.12






FIG. 12A









FIG.15



FIGI6




FIG.17


							_
TV 182 GUIDE 193		8:30p	Blossom	3			
481		8:00p	Fresh Prince	Murphy Brown	JFK	Day One	
	30-7:30p)	7:30p	Ent. Tonight	Major Dad	Own Words	Wheel of Fortune	
	4 KRON Baseball (4:30-7:30p)	7:00p	Baseball	Evening Shade	JFK: In His Own Words	Jeopardy!	
AII~ <i>®</i> Listings	4 KBON	Today	4 KRON 185	5 KPIX	6 HBO:	7 KG0	
							_

FIG 18


									ш
TV Guide 5:45 pm	Children	Ξ		⊟		=	Ξ		
S By   Enter   1905	News   Sports   News   C	22 LIF 4:00p A Case of DeadlyForce	HOT   4:00p Ring of Fire II:Blood and Steel	34 AMC 4:00p Texas Across the River	31 MAX 34:00p The Ballad of the Sad Cafe	8 SHO 5:00p Big Girls Don't Cry-They Get Even		25 TBS 5 05p No Mercy	

45

			-203								FIG 2
TV 182	NIC O'SU DITE - 1/63				¥		E				
Listings By Solution Enter Channel 322 2004	3 PREV 4KRON 5 H	Today	4:30p Baseball	7:30p Entertainment Tonight	8:00p Fresh Prince	8:30p Blossom	9:OOpPerryMason: Notorious Nun	II:OOp News	11:30 Tonight	12:30a David Letterman	



F16.21






FIG.23




FIG.24

Pay Per View Confirmation



You have requested to order:

Passenger 57

\$3.99

Yes, I would like to order

Passenger 57 has been Ordered! Tune to Channel I Today at 9:00pm.



FIG.24A

LIST	INGS	7	Listi	ing ⊲I	> 6	:06PA	JG 16
5:00	5:30	6:00	6:30	7:00	7:30	8:00	
CBS Fox PBS COM HBO ESN AMI		News News CBS I Club Myst Tribu Grem Tenni Ariss Natur I Love	News Paradery! te to ( lins 2: is (4:3) my L ral Wo	Carson The N O) ove (5 orld	n Iew B	atch	

FIG.25

Premium Ent	er MSO LOGO 5:03pm
HBO Home Box Office \$10	
SHO Showtime \$9.95/M	onth
DIS The Disney Channe	1 \$9.95/Month
TMC The Movie Channel	
MAX Cinemax \$9.95/Mo	
PLA Playboy at Night \$4.	95/Evening(5:00pm to 3:00am
ACT Action \$5.95/Day(1)	:00pm to 3:00pm)
Movie, special events, and fami	
You are not a Subscriber. Press	
·	

FIG.26




FIG.27

Cable System Messages 5:52 pm	
Pay Per View is featuring "Batman Returns" this month. Get a free sneak peek of HBO this weekend.	
Complete MSO Title	

FIG.28





FIG. 28A

Billing Billing
Name: TV Guide Onscreen Acct.#; [12345-098765-08-9] Billed From: (05/25/93) Billed To: (06/25/93) Total: \$3.99
FOR CUSTOMER SERVICE CALL: 790-0900
Date Time Service / PPV Event Cost
06/07/93 9:00 p PASSENGER 57 \$3.99

FIG



**FIG.30** 




FIG. 31

Quote         Watch         Ess           Alarms         Symbol         Last         Vol(100s)         Ch           CMCSA         18         5415         -0.2           CVC         29.75         129         -0.1           CVC         29.75         129         -0.1           JOIN         10.5         22         0           LBTYA         18.125         873         0.62           LBTYB         18         0         1.5           TCOMA         18.25         22970         -0.5           TCOMB         19.25         51         -0.37           TUNE         5.375         407         -0.12
Quoi

FIG. 32




FIG. 33

STORIES

XPRES Jun 7

# **US World News**

Cubans use Vitamins to combat epidemic

Geneva - A costly campaign to provide vitamins to all Cubans has helped curb a mysterious epidemic that has afflicted thousands with vision problems, a World Health Organization offical said yesterday.

The outbreak of optical neuritis has dimmed the vision of about 20,000 Cubans and a related malady has affected 6,000 other people, mostly women.

FIG.34

# SPORTS


5:54 pm

Major League Baseball

Yesterday in National League Action Colorado 7, Houston 5 San Francis co 5, Chicago 4

Yesterday in American League Action Detroit 4, Boston 1 Toronto 4, Milwaukee 2

**FIG.35** 






FIG 36B




FIG. 36C




FIG. 36D

	20	7	
LOCA	TOR	$\boxtimes$	
2 KWGN	3PPV	4 KCNC	٥
4I ABE	3 AMC	24 BET	4
21DIS	I8ENC	14 HBO	4
II REQI	I5REQ2		
Clear A	LL favorite	channels	
	included	Excluded	
	2 KWGN 4I ABE 2IDIS II REQI Clear A	LOCATOR  2KWGN 3PPV  4I ABE 3AMC 2IDIS IBENC II REQI I5REQ2 Clear ALL favorite	2 KWGN 3PPV 4 KCNC 4I ABE 3AMC 24 BET 2IDIS IBENC 14 HBO II REQI I5REQ2 Clear ALL favorite channels annel Included Excluded

FIG. 37




FIG.38




FIG.38A

<u> </u>		(ds)	2m)		<u> </u>	code.	
TODAY 7:30PM	Gov't Program(IO-IOa)	52 SPICE Mom and Dad Save the World (4-6p)	Religious Programming(12—12m)	Public Access (I2-I2m)	NBA Basketball (6-30-9p)	Non and Dad Save the World \$4.99  You have requested this program at 4PM. To complete the ordering process, The organise code.  Purchase Code: [xxxx]	
GUIDE	SICSPN2	52 SPICE	53 KWHD	54 MUN2	2 KWGN	Mom and Dad You have requ	

FIG. 38B

TV				
Movie Rating: Parental Guidonce:	1 PG  Adult The	PG-I3	R Situations	<b>D</b>
	4 2KWGN	3PPV program or series	4 KONC É	] >
Lockout Code:	Clear		ange	

FIG. 39




FIG. 40



You do not have a

8:32 PM

Lockout Code set.
To restrict the availability
of certain channels or programs, use your remote to enter four digits (for example, 4567).

Lockout Code: (\* \* \* \*

# FIG.40A





To restrict the ability to order programming, use your remote to enter four digits (for example, 1234),

Purchase Code: (\* \* \* \*

FIG.40B




FIG.40C




FIG.40D







FIG.41



(11) EP 1 558 028 A3

(12)

#### **EUROPEAN PATENT APPLICATION**


(88) Date of publication A3: 17.08.2005 Bulletin 2005/33

(51) Int CL7: H04N 5/445

- (43) Date of publication A2: 27.07.2005 Bulletin 2005/30
- (21) Application number: 05075996.8
- (22) Date of filing: 20.05.1994
- (84) Designated Contracting States:

  AT BE CH DE DK ES FR GB GR IE IT LI LU MC NL
  PT SE
- (62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC: 04075599.3 / 1 443 756 00200915.7 / 1 028 590
- (71) Applicant: United Video Properties Inc. Tulsa, Oklahoma 74136-5422 (US)
- (72) Inventor: The designation of the inventor has not yet been filed
- (74) Representative: Neobard, William John Kilburn & Strode 20 Red Lion Street London WC1R 4JP (GB)
- (54) Improved electronic television program schedule guide system and method
- (57) An electronic program schedule system which includes a receiver for receiving broadcast, satellite or cablecast television programs for a plurality of television channels and a tuner for tuning a television receiver to a sectled one of the plurality of channels. A data processor receives and stores in a memory television program schedule inforamtion for a plurity of television channels. A user control appratus, such as a remote controller, is utilised by a viewer to choose user control commands and transmit signals in response to the data processor which receives the signals in response to user control commands. A television receiver is used to display the television programs and televisi

inforamtion. A video display generator receives video control commands from the data processor and program schedule inforamtion from the memory and displays a portion of the program schedule information in overlaying relationship with a television program appearing on a television channel in at least one mode operation of the television programing guide. The data processor controls the video display generator with video control commands, issued in response to the user control commands, to display program schedule information for any chosen one of the plurality of television programs in the programs in chedule information for any chosen one of the plurality of television programs then appearing on any other chosen one of the plurality of channels on the television programs in even the television programs in one of the plurality of channels on the television procesiver.





# EUROPEAN SEARCH REPORT

Application Number EP 05 07 5996

Category	Citation of document with indic of relevant passages	ation, where appropriate,	Relevant to claim	CLASSIFICATION OF TH APPLICATION (Int.CL7)
A	US 4 706 121 A (YOUNG 10 November 1987 (198 * page 15, line 20 -	7-11-10)	1,3,5,7, 9,11,13, 15,17	H04N5/445
A	WO 92/04801 A (INSIGH 19 March 1992 (1992-0 * page 10, line 6 - p	3-19)	1,3,5,7, 9,11,13, 15,17	
				TECHNICAL FIELDS SEARCHED (Int.Cl.7)
	The present search report has been o	rawn up for all claims  Dae of computer of the seuten		Exertine
T	he Hague	22 June 2005	Verso	helden. J
X : particul Y : particul docume	EGORY OF CITED DOCUMENTS larly relevant if taken alone larly relevant if combined with another int of the same category opical background	T theory or proper	ple underlying the inver- ocument, but published ate	

#### ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 05 07 5996

This annex lists the patient family members relating to the patient documents colled in the above-mentioned European search report. The members are as contained in the European Patient Office EDP tile on The European Patient Office is in no way liable for these particulars which are merely given for the purpose of information.

22-06-2005

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 470612	L A	10-11-1987	NO	NE	duic
WO 9204801	Α.	19-03-1992	AT	070000 =	
		20 00 1002		270808 T	15-07-200
			AT	287175 T	15-01-200
			AT	191596 T	15-04-200
			AT	220273 T	15-07-200
			CA	2091160 A1	
			CA	2284587 A1	11-03-199
			CA		11-03-199
			CA	2420426 A1	11-03-199
				2499751 A1	11-03-199
			CA	2499757 A1	11-03-199
			CA	2499761 A1	11-03-199
			CA	2499765 A1	11-03-199
			DE	69132096 D1	
			DF	69132096 T2	11-05-200
			DE	69133060 D1	16-11-200
			DE	69133060 T2	08-08-200
			DF		06-03-200
			DE	69133404 D1	12-08-200
				69133439 D1	17-02-200
			DK	548286 T3	11-09-200
			DK	969662 T3	28-10-200
			EΡ	1111912 A1	27-06-200
			EP	1244300 A1	
			EP	1337108 A1	25-09-2002
			EP	0548286 A1	20-08-2003
			ĒΡ		30-06-1993
			ES		05-01-2000
			ES	2223395 T3	01-03-2005
			ES	2144402 T3	16-06-2000
			F2	2180253 T3	01-02-2003
			GR	3033659 T3	31-10-2000
			JP	3098215 B2	16-10-2000
			JP	10208328 A	07-08-1998
			JP	6504165 T	07-00-1998
			JP	3600149 B2	12-05-1994
			JΡ	2001186438 A	08-12-2004
			JΡ		06-07-2001
			US	2004088792 A	18-03-2004
				5353121 A	04-10-1994
			US	5727060 A	10-03-1998
			US	2002186959 A1	12-12-2002
			WO .	9204801 A1	19-03-1992
			US	6216265 B1	10-04-2001
			US	2003159147 A1	21-08-2003
			US	5479268 A	21-08-2003
				5532754 A	26-12-1995
		ì	15	5332/34 A	02-07-1996
			10	5790198 A	04-08-1998
nore details about this annex			در	5619274 A	08-04-1997

#### EP 1 558 028 A3

#### ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 05 07 5996

This arrors that the pulser family promisers relating to the patient documents cited in the above-mentioned European search report. The members are an continuised mits either district of those EDP files on. The European Patient Office is in no way liable for these particular which are merely given for the purpose of information.

Patent document afted in search report	Publication date		Patent family member(s)		Publication date
WO 9204801 A		US US US US US US	6167188 2001012439 2003185545 5949954 5479266 5809204	A1 A1 A A	26-12-20 09-08-20 02-10-20 07-09-19 26-12-19 15-09-19

E For more details about this annex : see Official Journal of the European Patent Office, No. 12/82